



SECPS – Sediment and Erosion Control Construction Plan Submittal Checklist

Project Name _____ Watershed _____ Jurisdiction _____

Project Acreage _____ Proposed Impervious _____ Disturbed Acreage _____

Applicant:

Name _____

Address: 6200 Falls of Neuse Road, Suite 10
 Raleigh, NC 27609

Phone: _____

Email: _____

Engineer:

Name: _____

Address: _____

Phone: _____

Email: _____

Construction Plan Review Submittal Package Requirements

[10-30-2(B)]-The S&EC plan submittal package must include all applicable items below to demonstrate compliance with applicable regulations. Unless otherwise noted, all references shown in brackets are for the *Wake County Unified Development Ordinance (UDO)*, adopted 04/17/06. Select all applicable items below and provide with the submittal.

<input type="checkbox"/>	1.	Erosion Control and Stormwater Joint Application (Required to initiate processing)
<input type="checkbox"/>	2.	Review Fees (Required to initiate processing) RESUBMITTALS: The first resubmittal is free, but all subsequent resubmissions require a \$75 Resubmission Fee
<input type="checkbox"/>	3.	[10-30-2(B)(2)] Notarized Wake County Financial Responsibility/Ownership Form (Required to initiate processing)
<input type="checkbox"/>	4.	Other documents:
<input type="checkbox"/>	a.	WC ONLY PRELIMINARY ZONING AND SUBDIVISION APPROVAL: Copy of approval notification (property description, subdivision or COSD approval, or Board of Adjustment approval, etc.).
<input type="checkbox"/>	b.	WC ONLY FLOOD STUDY: Copy of approval notification from Wake County Flood & Stormwater Environmental Engineer, (if applicable)
<input type="checkbox"/>	c.	ENGINEERING APPROVAL: Copy of approval notification for projects in a municipality's zoning jurisdiction
<input type="checkbox"/>	d.	401/404 Documentation (Buffer determination letters, PCN application, comments, and approval)
<input type="checkbox"/>	e.	NCDOT Approval
<input type="checkbox"/>	f.	Encroachment agreement(s) completed, signed and notarized for all off-site construction
<input type="checkbox"/>	5.	Cover letter stating the purpose of the submission RESUBMITTALS: A letter detailing any changes, comments, proposed solutions to review comments, etc.
<input type="checkbox"/>	6.	Copy of the USGS Quad Map with delineated project limits
<input type="checkbox"/>	7.	Copy of the Wake County Soil Survey map with delineated project limits



SECPS – Sediment and Erosion Control Construction Plan Submittal Checklist

<input type="checkbox"/>	8.	Drainage Area Map showing drainage areas to erosion control devices
<input type="checkbox"/>	9.	1 set of Erosion Control Calculations:
	<input type="checkbox"/>	a. Sediment basin design (See website for Wake County design criteria)
	<input type="checkbox"/>	b. Ditches, swales, and channels: Q10/V10. Tractive force (shear stress), capacity and geometry.
	<input type="checkbox"/>	c. Dissipaters: Q10 velocities, stone size and dimensions. [10-21-4]
CLOSED SYSTEM	<input type="checkbox"/>	d. Velocity calculations for stormwater runoff at points of discharge resulting from a 10-year storm after development [10-21-3]
<input type="checkbox"/>	10.	One(1) copy of a complete set of construction drawings for 1 st submission, five (5) copies for approval
<input type="checkbox"/>	11.	Proposed Site Plan:
	<input type="checkbox"/>	a. Location/Vicinity Map
	<input type="checkbox"/>	b. North arrow, graphic scale, drafting version date, legend and professional seal
	<input type="checkbox"/>	c. Existing and proposed contours: plan and profiles for roadways
	<input type="checkbox"/>	d. Boundaries of tract: including project limits
	<input type="checkbox"/>	e. Limits of disturbance specified on plan
	<input type="checkbox"/>	f. Proposed improvements: roads, buildings, parking areas, grassed landscaped, and natural areas.
	<input type="checkbox"/>	g. Lot lines, lot numbers and road names
	<input type="checkbox"/>	h. Utilities: community water and sewer, plan/profiles, easements and sediment controls.
	<input type="checkbox"/>	i. Stormwater Network: inlets, culverts, swales, ditches, channels and drainage easements.
	<input type="checkbox"/>	j. TEMPORARY SEDIMENT CONTROLS: locations and dimensions of gravel entrances, diversion ditches, silt fence, sediment basins, inlet protection, etc.
	<input type="checkbox"/>	k. PERMANENT EROSION CONTROLS: locations and dimensions of dissipaters, ditch linings, armoring, level spreaders, retaining walls, etc.
	<input type="checkbox"/>	l. Location and requirements for stockpiles (see website for Stockpile Requirements)
	<input type="checkbox"/>	m. Wake County Construction Details
	<input type="checkbox"/>	n. Wake County Construction Sequence
	<input type="checkbox"/>	o. Wake County Stabilization Guidelines



SECPS – Sediment and Erosion Control Construction Plan Submittal Checklist

	<input type="checkbox"/>	p.	Wake County Basin Removal Sequence Wake County or jurisdictional municipality must grant permission to convert the sediment basin over to stormwater use prior to completing any related work (a note in the construction sequence or elsewhere on the plan should indicate this).
	<input type="checkbox"/>	q.	Show all Riparian Buffers [Article 9-21]; (Neuse: [15A NCAC 02B.0233 & 0242])
	<input type="checkbox"/>	r.	Delineation of current FEMA boundaries (floodway, flood fringe & future/0.2%)
	<input type="checkbox"/>	s.	Delineation of flood prone soil areas
	<input type="checkbox"/>	t.	Location and type of all proposed stormwater management structures (<i>grass swale, wet/dry detention basin, filtering/infiltration basin, bioretention, etc.</i>)

Standards and Requirements

By marking items with an "X", applicant acknowledges potential standards to be applied to the proposed development.

Wake County UDO Article 10 - Erosion and Sedimentation Control Requirements

<input type="checkbox"/>	12.	Erosion Control: This project will require a Land Disturbance Permit if it involves <u>greater than one acre of disturbance</u> . See website for details.
<input type="checkbox"/>	13.	10-20-1 Minimum Standards - All soil erosion and sedimentation control plans and measures must conform to the minimum applicable standards specified in <i>North Carolina's Erosion and Sediment Control Planning and Design Manual</i> and the <i>Wake County Sedimentation and Erosion Control Plan Review Manual</i> . Erosion control devices must be installed to prevent any offsite sedimentation for any construction site regardless of the size of the land disturbance.
<input type="checkbox"/>	14.	10-20-3 Operation in Lakes or Natural Watercourses -Land disturbing activity in connection with construction in, on, over, or under a lake or natural watercourse must minimize the extent and duration of disruption of the stream channel. Where relocation of a stream forms an essential part of the proposed activity, the relocation must minimize unnecessary changes in the stream flow characteristics.
<input type="checkbox"/>	15.	10-20-10 Standards for High Quality Water (HQW) Zones Land-disturbing activities to be conducted in High Quality Water Zones must be designed as follows:
<input type="checkbox"/>	a.	Uncovered areas in High Quality Water (HQW) zones must be limited at any time to a maximum total area of 20 acres within the boundaries of the tract.
<input type="checkbox"/>	b.	Maximum Peak Rate of Runoff - Erosion and sedimentation control measures, structures, and devices within HQW zones must be planned, designed and constructed to provide protection from the runoff of the 25-year storm.
<input type="checkbox"/>	c.	Settling Efficiency - Sediment basins within HQW zones must be designed and constructed so that the basin will have a settling efficiency of at least 70% for the 40 micron (0.04mm) size soil particle transported into the basin by the runoff of that 2-year storm which produces the maximum peak rate of runoff.
<input type="checkbox"/>	d.	Grade - The angle for side slopes must be sufficient to restrain accelerated erosion (side slopes no steeper than 2 horizontal to 1 vertical if a vegetative cover is used for stabilization unless soil conditions permit a steeper slope or where the slopes are stabilized by using mechanical devices, structural devices or other acceptable ditch liners)



SECPs – Sediment and Erosion Control Construction Plan Submittal Checklist

<input type="checkbox"/>	16.	Riparian Buffer Rules:	
	<input type="checkbox"/>	a.	Due to the location of this project, it should be noted that a rule to protect and maintain existing buffers along watercourses in the Neuse River Basin became effective on July 22, 1997. The Neuse River Riparian Area Protection and Maintenance Rule (15A NCAC 2B.0233) applies to all perennial and intermittent streams, lakes, ponds and estuaries in the Neuse River Basin with forest vegetation on the adjacent land or "riparian area".
	<input type="checkbox"/>	b.	Due to the location of this project, it should be noted that a rule to protect and maintain existing buffers along watercourses in the Jordan Lake Watershed became effective on August 11, 2009. The Jordan Lake Water Supply Watershed Buffer Rules (15A NCAC 02B .0267) applies to all perennial and intermittent streams, lakes, ponds and estuaries in the Jordan Lake Watershed with forest vegetation on the adjacent land or "riparian area".
<input type="checkbox"/>	17.	Senate Bill 1020; "SECTION 3.(h) Additional standards for land-disturbing activities in the water supply watershed":	
	<input type="checkbox"/>	a.	Erosion and sedimentation control measures, structures, and devices shall be planned, designed, and constructed to provide protection from the runoff of the 25-year storm
	<input type="checkbox"/>	b.	Sediment basins shall be planned, designed, and constructed so that the basin will have a settling efficiency of at least seventy percent (70%) for the 40-micron size soil particle transported into the basin by the runoff of the two-year storm that produces the maximum peak rate of runoff
	<input type="checkbox"/>	c.	Newly constructed open channels shall be planned, designed, and constructed with side slopes no steeper than two horizontal to one vertical if a vegetative cover is used for stabilization unless soil conditions permit steeper slopes or where the slopes are stabilized by using mechanical devices, structural devices, or other acceptable ditch liners.

Applicant Signature: 

Date: 6/23/2020