

CLIENT

Stanley Martin Homes 4020 Westchase Blvd, Suite 470 Raleigh, NC 27607 919–724–0624 Attn: Brian Ketchem

SURVEYOR

Bass, Nixon & Kennedy, Inc. 6310 Chapel Hill Rd, Suite 250 Raleigh, NC 27604 919–851–4422 Attn: Dan Gregory, PLS

SITE ENGINEER

McAdams 2905 Meridian Parkway Durham, NC 27713 919-475-6439 Attn: Todd O'Daniel, PE

ROADWAY ENGINEER

Exult Engineering 24 Cabarrus Avenue East, Suite 3000 Concord, NC 28025 980-495-2249 Attn: Elizabeth Lynch, PE

SHEET NO.	DESCRIPTION	
1	TITLE SHEET	
2	CONVENTIONAL SYMBOLS	
3	PROJECT NOTES	
4A thru 4C	TYPICAL SECTIONS	
5A thru 5D	DETAILS	
6	TRAFFIC MANAGEMENT PLAN	
EX–1 thru EX–7	EXISTING CONDITIONS SHEETS	
R–1 thru R–7	PLAN SHEETS	
R-8 thru R-12	PROFILE SHEETS	
SD-1 thru SD-4	INTERSECTION SIGHT DISTANCE SHEETS	
EC-1 thru EC-19	EROSION CONTROL SHEETS	
PM-1 thru PM-7	PAVEMENT MARKING AND SIGNING SHEETS	
X-1 thru X-46	ROADWAY CROSS SECTIONS	

 \bigcirc

PEARCE FARM



State Line	
County Line	
Township Line	
City Line	
Reservation Line	· · ·
Property Line	
Existing Iron Pin	
Computed Property Corner	
Property Monument	·
Parcel/Sequence Number	(l23)
Existing Fence Line	xxx
Proposed Woven Wire Fence	-
Proposed Chain Link Fence	
Proposed Barbed Wire Fence	
Existing Wetland Boundary	
Proposed Wetland Boundary	
Existing Endangered Animal Boundary —	EAB
Existing Endangered Plant Boundary ——	——— ЕРВ ————
Existing Historic Property Boundary	нрв ———
Known Contamination Area: Soil	<u> </u>
Potential Contamination Area: Soil	<u> </u>
Known Contamination Area: Water	— - 😿 — w — 😿
Potential Contamination Area: Water ——	w%
Contaminated Site: Known or Potential —	

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap ———	0
Sign	⊙ s
Well	O W
Small Mine ————	☆
Foundation ————	
Area Outline	
Cemetery	†
Building	
School	
Church	
Dam	
HYDROLOGY:	
Stream or Body of Water	
Hydro, Pool or Reservoir	
Jurisdictional Stream	JS
Buffer Zone 1	——— BZ 1 ———
Buffer Zone 2	———— BZ 2 ————
Flow Arrow	<
Disappearing Stream>	
Spring (
Wetland	1
Proposed Lateral, Tail, Head Ditch ————	
False Sump	${\longleftrightarrow}$

STATE CON RAILROADS:

Standard Gauge — RR Signal Milepost — Switch – RR Abandoned —— RR Dismantled ——

RIGHT OF WA

Secondary Horiz and Primary Horiz Contro Primary Horiz and V Exist Permanent Easn New Permanent Eas Vertical Benchmark Existing Right of Way Existing Right of Way New Right of Way L New Right of Way Li New Right of Way Li Concrete or Gran New Control of Acce Concrete C/A Ma Existing Control of Ac New Control of Acce Existing Easement Lin New Temporary Cor New Temporary Dro New Permanent Dra New Permanent Dra

New Permanent Util New Temporary Util New Aerial Utility Ea

ROADS AND

Existing Edge of Pave Existing Curb —— Proposed Slope Stak Proposed Slope Stak Proposed Curb Ram Existing Metal Guard Proposed Guardrail Existing Cable Guide Proposed Cable Guid Equality Symbol – Pavement Removal **VEGETATION:** Single Tree —— Single Shrub ———

 \bigcirc

Note: Not to S	AL PL	AN SHEEL SYMBC U.E. = Subsurface Utility Engineering	VLS
		Hodao — — — — — — — — — — — — — — — — — — —	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
	CSX TRANSPORTATION	Heage	
	MILEPOST 35	Orchard	ය ය ය
	Switch	Vinevard ———	
V & PROIECT CO	NTROL ·	MAJOK: Bridge Tuppel or Box Culvert	CONC
Vert Control Point —		Bridge, Tunnel of Box Colvert	
D Point			J come """ (
Vert Control Point		Head and End Wall	CONC HW
ent Pin, and Can	$\overset{\bullet}{\overset{\bullet}{\overset{\bullet}{}}}$	Pipe Culvert	
ement Pin and Can —	\sim	Footbridge ————————————————————————————————————	
		Drainage Box: Catch Basin DL or IB	Св
[,] Marker ———		Paved Ditch Gutter	
/ Line		Storm Sewer Manhole	S
ine		Storm Sewer	s
ine with Pin and Cap—		UTILITIES:	
ine with		POWER:	
ite R/W Marker		Existing Power Pole	•
ss Line with		Proposed Power Pole	6
cess —		Existing Joint Use Pole	
ss		Proposed Joint Use Pole	-0-
e	• • • • • • • • • • • • • • • • • • •	Power Manhole	P
nstruction Easement –	E	Power Line Tower —	\boxtimes
inage Easement		Power Transformer	\bowtie
inage Easement	• = = PDE	U/G Power Cable Hand Hole	
inage / Utility Easement	DUF	H–Frame Pole	•—•
ity Easement	PUE	U/G Power Line LOS B (S.U.E.*)	— — — P— — — —
ity Easement	TUE	U/G Power Line LOS C (S.U.E.*)	P P
isement	AUE	U/G Power Line LOS D (S.U.E.*)	P
DELATED EEATID	EC.	TELEPHONE:	
KELAIED FEAIUKI	CS :	Existing Telephone Pole	-•-
		Proposed Telephone Pole	-0-
	C	Telephone Manhole	\bigcirc
	F	Telephone Pedestal	Ī
		Telephone Cell Tower	, Ē,
rail		U/G Telephone Cable Hand Hole	HH
		U/G Telephone Cable LOS B (S.U.E.*)	T
arail —		U/G Telephone Cable LOS C (S.U.E.*)	T
derail ———		U/G Telephone Cable LOS D (S.U.E.*)	T
		U/G Telephone Conduit LOS B (S.U.E.*)	tc
		U/G Telephone Conduit LOS C (S.U.E.*)	TC
		U/G Telephone Conduit LOS D (S.U.E.*)	TC
	ŝ	U/G Fiber Optics Cable LOS B (S.U.E.*)	— — — — T FO— — — ·
	ය ස	U/G Fiber Optics Cable LOS C (S.U.E.*)——	T FO
	~	U/G Fiber Optics Cable LOS D (S.U.E.*)	T F0

WATER: Water Manhole Water Meter Water Valve		Image: Non-Structure Image: Structure Image: Structure
Water Hydrant U/G Water Line LOS B (S.U.E*) U/G Water Line LOS C (S.U.E*) U/G Water Line LOS D (S.U.E*)	₩	MENTS AROLINA
Above Ground Water Line		С С К С П К
TV: TV Pedestal TV Tower U/G TV Cable Hand Hole U/G TV Cable LOS B (S.U.E.*) U/G TV Cable LOS C (S.U.E.*) U/G TV Cable LOS D (S.U.E.*) U/G Fiber Optic Cable LOS B (S.U.E.*) U/G Fiber Optic Cable LOS C (S.U.E.*)	□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	PEARCE FAF ROADWAY IMPRO ROLESVILLE, NORTH
U/G Fiber Optic Cable LOS D (S.U.E.*)		
GAS: Gas Valve Gas Meter U/G Gas Line LOS B (S.U.E.*) U/G Gas Line LOS C (S.U.E.*) U/G Gas Line LOS D (S.U.E.*) Above Ground Gas Line SANITARY SEWER: Sanitary Sewer Manhole Sanitary Sewer Cleanout U/G Sanitary Sewer Line Above Ground Sanitary Sewer SS Forced Main Line LOS B (S.U.E.*)	 Image: Construction of the second seco	CONVENTIONAL SYMBOLS
SS Forced Main Line LOS C (S.U.E.*) SS Forced Main Line LOS D (S.U.E.*) MISCELLANEOUS: Utility Pole Utility Pole with Base	FSS	DEPARTA OF TRANSPORT
Utility Located Object Utility Traffic Signal Box Utility Unknown U/G Line LOS B (S.U.E.*) U/G Tank; Water, Gas, Oil Underground Storage Tank, Approx. Loc. A/G Tank; Water, Gas, Oil Geoenvironmental Boring U/G Test Hole LOS A (S.U.E.*) Abandoned According to Utility Records End of Information		JOB NO.: 00103002 DESIGNED BY: R. MANK DATE: 102324 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT. DATE SHEET NO.

2024 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch – N. C. Department of Transportation – Raleigh, N. C., Dated January, 2024 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
200.02	Method of Clearing – Method II
225.02	Guide for Gradina Subarade – Secondary and Local
225.04	Method of Obtaining Superelevation – Two Lane Pavement
225.06	Method of Gradina Sight Distance at Intersections
300.01	Method of Pine Installation
310.02	Parallel Pine End Section – Precast Concrete Section for 15" to $24"$ Pine
310.02	Cross Pine End Section – Precast Concrete Section for 18" to 30" Pine
310.00	Driveway Pine Construction
560.01	Mothed of Shoulder Construction High Side of Superclayated Curve Method I
654 01	Prevement Panairs
700.05	Tuing Proposed Payament to Existing
229 01	Concrete Endwall for Single and Double Pine Culverts 15" thru 18" Pine 90 Skow
840.00	Concrete Base Pad for Drainage Structures
840.00	Brick Catch Basin 12" thru 54" Pine
040.01 940.02	Direct Cartab Pasin $-12^{\prime\prime\prime}$ thru $54^{\prime\prime\prime}$ Pina
040.02 940.02	Concrete Calch Dasin – 12 miles on Strandard Catch Proin
040.03	Frame, Grates and Hood – for Use on Standard Catch Dasin
840.04	Concrete Open Inroat Catch Basin – 12 thru 48 Pipe
840.05	Brick Open Inrodi Catch Basin – 12° thru 48° Pipe
840.14	Concrete Drop Inlet – 12 thru 30 Pipe
840.15	Brick Drop Inlet – 12° thru 30° Pipe
840.16	Drop Inlet Frame and Grates – for use with Std. Dwg 840.14 and 840.15
840.17	Concrete Grated Drop Inlet Type 'A' – 12" thru 72" Pipe
840.18	Concrete Grated Drop Inlet Type 'B' – 12" thru 36" Pipe
840.19	Concrete Grated Drop Inlet Type 'D' – 12" thru 36" Pipe
840.31	Concrete Junction Box – 12" thru 66" Pipe
840.32	Brick Junction Box – 12" thru 66" Pipe
840.34	Iraffic Bearing Junction Box – for Use with Pipes 42" and Under
840.35	Traffic Bearing Grated Drop Inlet – for Cast Iron Double Frame and Grates
840.36	Traffic Bearing Grated Drop Inlet – for Steel (840.37) Double Frame and Grates
840.37	Steel Grate and Frame
840.45	Precast Drainage Structure
840.46	Traffic Bearing Precast Drainage Structure
840.51	Brick Manhole – 12" thru 36" Pipe
840.52	Precast Manhole – 4', 5' and 6' Diameter
840.54	Manhole Frame and Cover
840.66	Drainage Structure Steps
840.71	Concrete and Brick Pipe Plug
840.72	Pipe Collar
846.01	Concrete Curb, Gutter and Curb & Gutter
848.01	Concrete Sidewalk
848.02	Driveway Turnout – Radius Type
848.03	Driveway Turnout – Drop Curb Type
848.04	Street Turnout
848.05	Curb Ramp – Proposed Curb & Gutter
850.01	Concrete Paved Ditches
852.01	Concrete Islands
852.02	Concrete Mountable Median – for Use with Rigid or Flexible Pavement
852.04	Method for Placement of Drop Inlets in Grassed Median – Using 1'–6" Curb and Gutte
852.05	Median Curb for Catch Basin – for Use with 1'–6" Curb and Gutter
852.10	Median Construction – with Curb and Gutter
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
862.04	Anchoring End of Guardrail – B–77 and B–83 Anchor Units
876.01	Rip Rap in Channels
876.02	Guide for Rip Rap at Pipe Outlets

GENERAL NOTES

- CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THESE PLANS, THE LATEST EDITIONS OF THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION (NCDOT) STANDARD DRAWINGS AND STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, THE NORTH CAROLINA EROSION AND SEDIMENT CONTROL HANDBOOK AND REGULATIONS, AND THE STANDARDS, SPECIFICATIONS AND GENERAL DESIGN STANDARDS OF THE LOCAL MUNICIPALITY AND AMENDMENTS OR SUPPLEMENTS THERETO. WHERE CONFLICTS EXIST BETWEEN ANY OF THESE STANDARDS, SPECIFICATIONS, OR PLANS, THE MOST STRINGENT SHALL APPLY UNLESS OTHERWISE NOTED IN THESE PLANS.
- CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL ENVIRONMENTAL 2. REGULATIONS, AND SHALL VERIFY OR OBTAIN ALL NECESSARY PERMITS AND APPROVALS PRIOR TO COMMENCING CONSTRUCTION. NCDOT ENCROACHMENTS SHALL BE OBTAINED BY THE ENGINEER. CONTRACTOR IS RESPONSIBLE FOR ADHERING TO ALL PROVISIONS SET FORTH IN THE THE APPROVED NCDOT DRIVEWAY PERMIT AND ENCROACHMENT AGREEMENTS.
- THE CONTRACTOR SHALL BE SOLELY RESPONSBILE FOR TRAFFIC MANAGEMENT ON ALL PUBLIC STREETS AND FOR ALL JOBSITE SAFETY THROUGHOUT CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE TRAFFIC CONTROL DEVICES, LANE CLOSURES, ROAD CLOSURES, POSITIVE PROTECTION AND/OR ANY OTHER WARNING OR POSITIVE PROTECTION DEVICES NECESSARY FOR THE SAFETY OF ROAD USERS DURING CONSTRUCTION AND ANY SUBSEQUENT MAINTENANCE. THIS SHALL BE PERFORMED IN CONFORMANCE WITH THESE PLANS AND THE LATEST NCDOT ROADWAY STANDARD DRAWINGS AND SPECIFICATIONS FOR ROADS AND STRUCTURES AND AMENDMENTS OR SUPPLEMENTS THERETO AND AS FURTHER DIRECTED BY THE LOCAL MUNICIPALITY AND STATE INSPECTORS. WHEN THERE IS NO GUIDANCE PROVIDED IN THE ROADWAY STANDARD DRWAINGS OR SPECIFICATIONS, COMPLY WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS AND AMENDMENTS OR SUPPLEMENTS THERETO. NOW WORK SHALL BE PERFORMED IN THE RIGHT OF WAY UNLESS THIS REQUIREMENT IS SATISFIED. THE CONTRACTOR SHALL NOT MAKE ANY LANES CLOSURES OR CHANGES TO THE EXISTING TRAVEL PATTERNS ON ANY PUBLIC STREET WITHOUT PRIOR APPROVAL FROM THE NCDOT AND THE LOCAL MUNICIPALITY.
- ANY PROPRIETARY PRODUCTS OR APPROVED ALTERNATES SPECIFIED IN THESE PLANS SHALL BE 4 INSTALLED PER THE MANUFACTURER'S SPECIFICATIONS.
- ENGINEER MUST BE NOTIFIED IN WRITING IMMEDIATELY OF ANY VARIATIONS OR AMBIGUITIES BETWEEN THE PLANS AND SPECIFCATIONS AND ACTUAL SITE CONDITIONS. ANY WORK DONE BY THE CONTRACTOR AFTER HIS DISCOVERY OF SUCH INCONSISTENCIES OR AMBIGUITIES IS AT THE CONTRACTOR'S RISK.
- THE CONTRACTOR SHALL CONDUCT A PRE-CONSTRUCTION CONFERENCE WITH NCDOT AND THE LOCAL MUNICIPALITY PRIOR TO COMMENCING CONSTRUCTION.

DEMOLITION AND GRADING NOTES

- THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACE AT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AND EXISTING PAVEMENT AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.
- THE CONTRACTOR SHALL REMOVE ALL TREES. STUMPS AND VEGETATIVE MATERIAL FROM THE RIGHT OF WAY AND DISPOSE OF IN A LICENSED LANDFILL OR DISPOSAL SITE UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL CONFORM TO ALL LOCAL. STATE, AND FEDERAL REQUIREMENTS REGARDING THE REMOVAL AND DISPOSAL OF MATERIALS AND DEBRIS.
- ALL MATERIALS USED FOR BACKFILL SHALL BE FREE OF WOOD, ROOTS, ROCKS, BOULDRES, OR ANY 3. OTHER NON-COMPATIBLE SOIL TYPE MATERIAL. UNSATISFACTORY MATERIALS ALSO INCLUDE MAN-MADE FILLS AND REFUSE DEBRIS DERIVED FROM ANY SOURCE.
- BACKFILL MATERIAL IS TO BE PLACED AT A MAXIMUM OF 6 INCH LOOSE LAYERS AND EACH LAYER 4. THOROUGHLY COMPACTED. ALL EMBANKMENT BACKFILL SHALL BE COMPACTED TO 95% DENSITY AND ALL SUBGRADE TO 100% DENSITY IN ACCORDANCE WITH AASHTO T-99 AS MODIFIED BY NCDOT. CONTRACTOR SHALL CLEAR AND GRUB THE SITE AND PLACE, COMPACT AND MOISTURE CONDITION ALL FILL PER THE GEOTECHNICAL ENGINEER'S SPECIFICATIONS AND ALL FILL MATERIAL SHALL BE APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACEMENT.
- 5. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING DRAINAGE PATTERNS AND PROVIDING POSITIVE DRAINAGE AT ALL TIME THROUGHOUT PROJECT CONSTRUCTION. THE CONTRACTOR SHALL USE INTERIM SILT FENCES, DIVERSION DITCHES, BERMS, OR OTHER METHODS AS REQUIRED TO DIRECT DRAINAGE TO BEST UTILIZE THE EROSION CONTROL DEVICES IN PLACE, AND TO PREVENT SILT AND CONSTRUCTION RUNOFF FROM DRAINING TO PROPERTIES OFFSITE. CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE STATE AND LOCAL EROSION CONTROL AND CONSERVATION ORDINANCES.
- TEMPORARY EROSION CONTROL DEVICES SHALL BE INSTALLED PRIOR TO THE START OF 6. CONSTRUCTION. REFER TO EROSION CONTOL PLANS FOR THE CLEARING LIMITS AND LOCATION AND TYPE OF DEVICES.

PAVING/CURBING

- 1.
- 2.
- 3.
- WITH JOINT SEALANT.
- 4.

UTILITY NOTES

- APPROXIMATE ONLY.
- 2 811.
- 3.
- CONSTRUCTION.

TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX

CITY OF RALEIGH - PLANS AUTHORIZED FOR CONSTRUCTION

Electronic Approval: This approval is being issued electronically. This approval is valid upon the signature of a City of Raleigh Review Officer below. The City will retain a copy of the approved plans. Any work authorized by this approval must proceed in accordance with the plans kept on file with the City. This electronic approval may not be edited once issued. Any modification of this approval once issued will invalidate this approval.

City of Raleigh Development Approval:

Raleigh Water Review Officer

PROVIDE 10* TRANSITION TO TIE PROPOSED CURB AND GUTTER TO THE EXISTING HEIGHT, WIDTH AND SHAPE OF EXISTING CURB AND GUTTER AT TIE-IN POINTS.

THE CONTRACTOR IS RESPONSIBLE FOR ENGINEERING AND SURVEY WORK REQUIRED FOR LINE AND GRADE CONTROL POINTS REQUIRED FOR EARTHWORK AND FOR STAKING OUT PAVEMENT AND ALL OTHER ITEMS IN THE PLANS.

ALL CURB JOINTS SHALL EXTEND THROUGH THE CURB AND ALL JOINTS SHALL BE SEALED

REMOVE EXISTING CONCRETE (WHERE REQUIRED) TO THE FIRST COLD JOINT OR SAW CUT TO OBTAIN A CLEAN EDGE FOR NEW CONSTRUCTION. SAW CUT EXISTING ASPHALT DRIVE AT LIMITS OF NEW CURBING TO OBTAIN A CLEAN EDGE.

PAVING SHALL BE IN ACCORDANCE WITH THE 2024 STANDARD SPECIFICATIONS SECTIONS 610, 1012 AND 1020. THE CONTRACTOR SHALL FOLLOW ALL PROCEDURES IN THE QUALITY MANAGMENT SYSTEM (QMS) FOR ASPHALT PAVEMENT AND MUST ADHERE TO ALL TESTING REQUIREMENTS AND QUALITY CONTROL REQUIREMENTS SPECIFIED IN THE ENCROACHMENT AND/OR DRIVEWAY PERMIT. THE NOMINATION OF THE TESTING LABORATORY AND THE PAYMENT OF SUCH TESTING SERVICES SHALL BE MADE BY THE OWNER. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO SHOW STANDARD TESTING PROCEDURES THAT THE WORK CONSTRUCTED DOES MEET THE REQUIREMENTS OF THE NCDOT SPECIFICATIONS.

ALL RAMPS SHALL COMPLY WITH THE LATEST NCDOT STANDARDS AND ADA REQUIREMENTS. CURB RAMPS ARE SHOWN ON THE PLANS AT THE APPROXIMATE LOCATIONS.

ALL CURVES ARE TO BE SUPERELEVATED IN ACCORDANCE WITH STD. 225.04 AND 225.05 USING THE RATE OF SUPERELEVATION RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE THE EXACT HORIZONTAL AND VERTICAL LOCATION (SHOWN OR NOT SHOWN) OF UTILITIES WITHIN THE PROJECT LIMITS. EXISTING UTILITY LOCATIONS AND SIZES SHOWN HAVE BEEN PROVIDED BY OTHERS AND ARE

CONTRACTOR SHALL NOTIFY THE NORTH CAROLINA 811 AT 1-800-632-4949 AT LEAST 72 HOURS PRIOR TO ANY DEMOLITION, GRADING OR CONSTRUCTION ACTIVITY FOR PROPER IDENTIFICATION OF EXISTING UTILITIES WITHIN THE SITE. CONTRACTOR TO CONTACT LOCAL UTILITIES THAT PROVIDE THEIR OWN LOCATOR SERVICES INDEPENDENT OF NORTH CAROLINA

RELOCATION OF EXISTING UTILITIES TO BE COORDINATED WITH LOCAL UTILITY PROVIDER(S).

THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING ALL UTILITY OWNERS AND FOR PROVIDING PROTECTION AND SAFEGUARDS TO PREVENT DAMAGE OR INTERRUPTION TO EXISTING FACILITIES AND TO MAINTAIN ACCESSIBILITY TO EXISTING UTILITIES. THE CONTRACTOR SHALL REPAIR, AT HIS OWN EXPENSE, ANY EXISTING UTILITIES DAMAGED DURING

WATER VALVE BOXES AND WATER METER BOXES THAT ARE ENCOUNTERED WITHIN THE PROJECT LIMITS ARE TO BE RAISED OR LOWERED TO MATCH THE ADJACENT FINISHED WORK (SEE SECTION 858-1 AND 1510 NCDOT SPECIFICATIONS).

These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued.

Public Works/Engineering

These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued.

Planning





	PAVEME	NT SCHEDULE			® H	- () Z	81 com	
	PROP. APPROX. 1½" ASF AT AN AVERAGE RATE OF	HALT CONCRETE SURFACE COURSE, TYPE S9.5C, 168 LBS. PER SQ. YD.	NC License 301 S. Main Street #C-4445 www.exultengineering.					
	PROP. APPROX. 3″ ASPHA AT AN AVERAGE RATE OF	LT CONCRETE SURFACE COURSE, TYPE S9.5C, 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS						
	PROP. VAR. DEPTH ASPHA AT AN AVERAGE RATE OF BE PLACED IN LAYERS NO	LT CONCRETE SURFACE COURSE, TYPE S9.5C, 112 LBS. PER SQ. YD. PER 1" DEPTH. TO T TO EXCEED $1\frac{1}{2}$ " IN DEPTH.						
	PROP. APPROX. 4" ASPHA TYPE I19.0C, AT AN AVE	LT CONCRETE INTERMEDIATE COURSE, RAGE RATE OF 456 LBS. PER SQ. YD.	S NA NA					
	PROP. VAR. DEPTH ASPHA TYPE I19.0C, AT AN AVE DEPTH, TO BE PLACED IN GREATER THAN 4" IN DEF	LT CONCRETE INTERMEDIATE COURSE, RAGE RATE OF 114 LBS. PER SQ. YD. PER 1" LAYERS NOT LESS THAN 2½" IN DEPTH OR TH.						
	PROP. APPROX. 5" ASPHA AT AN AVERAGE RATE OF	LT CONCRETE BASE COURSE, TYPE B25.0C, 570 LBS. PER SQ. YD.					U H	
	PROP. VAR. DEPTH ASPHA AT AN AVERAGE RATE OF BE PLACED IN LAYERS NO THAN 5½″ IN DEPTH.	LT CONCRETE BASE COURSE, TYPE B25.0C, 114 LBS. PER SQ. YD. PER 1" DEPTH. TO DT LESS THAN 3" IN DEPTH OR GREATER				RCE F IMPR	NORT	
	PROP. 10" AGGREGATE BA (MAY BE SUBSTITUTED FC	SE COURSE DR E1 IN AREAS WIDER THAN 6')				PEA WAY	LLE,	
	PROP. 2'-6" CONCRETE C	URB & GUTTER (NCDOT STD. 846.01)				SOAD	LESVI	
	PROPOSED 4" CONCRETE S	IDEWALK					S O	
	EARTH MATERIAL							
EXISTING PAVEMENT						CTIONS		
MILLING ASPHALT PAVEMENT, 1.5" DEPTH								
VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL THIS SHEET)						AL SE		
	NOTES: 1. PAVEMENT EDGE SLOPE 2. REFER TO PLAN SHEE 3. SAWCUT AND REMOVE E MINIMUM FULL DEPTH 4. WHEN E1 IS USED, US WHEN J1 IS USED, US	ES ARE 1:1 UNLESS SHOWN OTHERWISE. TS FOR VARIABLE WIDTHS. EXISTING ASPHALT PAVEMENT TO PROVIDE 1' ASPHALT PAVEMENT. SE 6" FROM BACK OF CURB TO 1:1 EDGE SLOPE. SE 12" FROM BACK OF CURB TO 1:1 EDGE SLOPE.				TYPIC/		
			D ,	RE ₽	NOT	SEAL TH CAR OFESSION SEAL USE FOR CO SEAL	OLINA DNA MARINE E.P. L.M.	
		TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX	DESIGNED BY: G. BOYLE	REVIEWED BY: E. LYNCH $_{ m \omega}$			D	
UTH he si ity w by th ept o be e l one	ORIZED FOR CONSTRUCTION al is being issued electronically. gnature of a City of Raleigh vill retain a copy of the approved his approval must proceed in on file with the City. This edited once issued. Any ce issued will invalidate this	These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval	JOB NO.: 00103002	DATE: 10/23/24	SCALE: $1'' = 50'$	KEVISIONS		
: App er	proval:	may not be altered once issued. Planning				SHEET N	0.	
			1					





C1
C2
D1
E1
J1
R1
S
Т
U
W



PAVEMENT SCHEDULE	© E
PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.	L L L L IN E E R I I N E E R I 1 S. Main Street napolis, NC 280 980.495.2250 xultengineering
PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS	
PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.	NC Lice
PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.	S INA
PROP. 10" AGGREGATE BASE COURSE (MAY BE SUBSTITUTED FOR E1 IN AREAS WIDER THAN 6')	AROL
PROP. 2'-6" CONCRETE CURB & GUTTER (NCDOT STD. 846.01)	
PROPOSED 4" CONCRETE SIDEWALK	
EARTH MATERIAL	PEA WAY ILLE,
EXISTING PAVEMENT	ROAD
MILLING ASPHALT PAVEMENT, 1.5" DEPTH	۳. ۳. ۲.
VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL SHEET 4A)	
 NOTES: 1. PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE. 2. REFER TO PLAN SHEETS FOR VARIABLE WIDTHS. 3. SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT TO PROVIDE 1' MINIMUM FULL DEPTH ASPHALT PAVEMENT. 4. WHEN E1 IS USED, USE 6" FROM BACK OF CURB TO 1:1 EDGE SLOPE. WHEN J1 IS USED, USE 12" FROM BACK OF CURB TO 1:1 EDGE SLOPE. 	TYPICAL SECTIONS
	SEAL PRELIMENT OF ESSION SEAL PRELIMENTARY PLANS DO NOT USE FOR CONSTRUCTION MGINEFR. MBETH W.
TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX THORIZED FOR CONSTRUCTION roval is being issued electronically. e signature of a City of Raleigh ty will retain a copy of the approved y this approval must proceed in pt on file with the City. This be edited once issued. Any once issued will invalidate this These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 10/23/24 REVIEWED BY: E. LYNCH SCALE: 1" = 50' INIT. DATE
Approval: by the Town of Wake Forest Planning Department. This approval may not be altered once issued.	SHEET NO.





TOWN OF ROLESVILLE: PSP-23-04

approval.















	ERS 1". HROUGHOU MONOLITH TERS AS HE BOTTO IPE IS S STANDARD ES OVER ANCE WIT TE AND B OF THE M IN TOP ENING IN TURE FROM NDARD DR/ F PRECAST	T. DIRECTED M SLAB. ET IN BA: NO. 840 3'-6" IN H STD. N RICK MAS ANHOLE (SLAB, AD TOP SLA TOP SLA I TOP OF AWING 840 BOX IS	2" KEYWA BY THE E SE SLAB (.00. DEPTH WI 0. 840.66 ONRY QUAN I.E. DIAG DITIONAL B.) BOTTOM SL 0.45 OR 8 USED.	AY, OR ENGINEER. DF BOX, TH STEPS 30NAL BAF VARIABLE LAB TO TO 40.46	AS E	1-24 STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH. N.C.
N	#4 BAR #4 EL BOXES					DARD DRAWING FOR JUNCTION BOX 10 66" PIPE
٩R	DS	TOTAL QU	ANTITIES	DEDUCTION	IS FOR ONE	HB H
X		BOX AND) SLABS	PIPE	CU.YDS.	LS L
	WALL/ FT. OF HT.	LBS. REINF	CU. YDS. MIN. "H"	C.S.	R.C.	AY 12'
7	0.185	22	0.750	0.015	0.024	N N
6	0.204	24	0.902	0.023	0.036	A C
7	0.222	30	1.065	0.033	0.049	5 2
6	0.259	40	1.434	0.059	0.085	
5	0.296	51	1.860	0.092	0.127	
3	0.333	64	2.341	0.132	0.178	
)	0.370	77	2.878	0.180	0.243	
3	0.407	111	3.623	0.235	0.317	
5	0.444	126	4.283	0.297	0.401	
2	0.481	145	5.090	0.367	0.495	SHEET 1 OF 1
0	0.518	169	5.917	0.444	0.589	940 21









 \sim

_

DR TO	ANGES MAY BE REQUIRED WHEN PHYSICAL DI AWINGS, STANDARD DETAILS, AND ROADWAY MEET FIELD CONDITIONS OR RESULT IN DU	MENSIONS IN THE DETAIL DETAILS ARE NOT ATTAINABLE PLICATE OR UNDESIRED	SIGNI K) INSTAL
OV SU EN	ERLAPPING OF DEVICES. MODIFICATION MA PPLEMENTING, COVERING, OR REMOVAL OF D GINEER.	Y INCLUDE: MOVING, EVICES AS DIRECTED BY THE	40 FT (3) DA
TH TH OR	E FOLLOWING GENERAL NOTES APPLY AT ALL E CONSTRUCTION PROJECT EXCEPT WHEN OTH DIRECTED BY THE ENGINEER.	TIMES FOR THE DURATION OF ERWISE NOTED IN THE PLAN	WHEN N WEEK, DIRECT
••••			L) PROVID
1	TIME RESTRICTIONS		M) INSTAL (W8-1)
A)	DO NOT CLOSE OR NARROW TRAVEL LANES AS	S FOLLOWS:	N) ENSURE
	SR 2049 (FORESTVILLE ROAD)	6:00 AM TO 9:00 AM	TRAFFI
	SR 2045/2051 (BURLINGTON MILLS ROAD)	4:00 PM TO 7:00 PM MONDAY THRU FRIDAY	TRAF
B)	DO NOT STOP TRAFFIC AS FOLLOWS:		O) WHEN L AREAS
	ROAD NAME	DAY AND TIME RESTRICTIONS	EXCEPT TRAVEL
	SR 2049 (FORESTVILLE ROAD) SR 2045/2051 (BURLINGTON MILLS ROAD)	6:00 AM TO 9:00 AM 4:00 PM TO 7:00 PM MONDAY THRU FRIDAY	SECTIO ADDITI
C)	DO NOT STOP TRAFFIC FOR MORE THAN 15 1	MINUTES WITHIN	PAVE
•)	THE PROJECT LIMITS.		P) INSTAL
	LANE AND SHOULDER CLOS	SURE REOUIREMENTS	UF NUA
D)	REMOVE LANE CLOSURE DEVICES FROM THE I PERFORMED BEHIND THE LANE CLOSURE OR N LONGER NEEDED OR AS DIRECTED BY THE E	LANE WHEN WORK IS NOT BEING WHEN A LANE CLOSURE IS NO NGINEER.	Q) PLACE SECOND APPLIC
E)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WO	ORKING WITHIN 15 FT OF AN	R) TIE PR LINES.
	OPEN TRAVEL LANE, CLOSE THE NEAREST OF STANDARD DRAWING NO. 1101.04 UNLESS THE BARRIER OR GUARDRAIL OR A LANE CLOSURI	PEN SHOULDER USING ROADWAY HE WORK AREA IS PROTECTED BY E IS INSTALLED.	S) REMOVE MARKER
F)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WO ADJACENT TO AN UNDIVIDED FACILITY AND OPEN TRAVEL LANE, CLOSE THE NEAREST OF STANDARD DRAWING NO. 1101.02 UNLESS TH BARRIER OR GUARDRAIL.	ORKING ON THE SHOULDER WITHIN 5 FT OF AN PEN TRAVEL LANE USING ROADWAY HE WORK AREA IS PROTECTED BY	T) PEDEST ADEQUA
	WHEN PERSONNEL AND/OR EQUIPMENT ARE WO TO A DIVIDEDFACILITY AND WITHIN 10 FT THE NEAREST OPEN TRAVEL LANE USING RO/ UNLESS THE WORK AREA IS PROTECTED BY B	ORKING ON THE SHOULDER ADJACENT OF AN OPEN TRAVEL LANE, CLOSE ADWAY STANDARD DRAWING NO. 1191,92 BARRIER OR GUARDRAIL.	U) LAW EN AREA A
G)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WO OF AN UNDIVIDED OR DIVIDED FACILITY, O THE TRAFFIC CONTROL PLANS, ROADWAY ST BY THE ENGINEER. CONDUCT THE WORK SO EQUIPMENT REMAIN WITHIN THE CLOSED TRA	ORKING WITHIN A LANE OF TRAVEL CLOSE THE LANE ACCORDING TO ANDARD DRAWINGS, OR AS DIRECTED THAT ALL PERSONELL AND/OR AVEL LANE.	V) IN THE TIE-IN THE EN AND BL 200 FT
H)	DO NOT WORK SIMULTANEOUSLY WITHIN 15 I TRAVELWAY, RAMP, OR LOOP WITHIN THE SA WITH GUARDRAIL OR BARRIER.	FT ON BOTH SIDES OF AN OPEN AME LOCATION UNLESS PROTECTED	W) ALL CU ON PAV COORDI
j	PAVEMENT EDGE DROP OFF	REOUIREMENTS	X) CONTRA THE PH
I)	BACKFILL AT A 6:1 SLOPE UP TO THE EDG PAVEMENT IN AREAS ADJACENT TO AN OPEN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:	E AND ELEVATION OF EXISTING ED TRAVEL LANE THAT HAS AN	SIDEWA BY THE HAS BE
	BACKFILL DROP-OFFS THAT EXCEED 2 INCH POSTED SPEED LIMITS OF 45 MPH OR GREA	ES ON ROADWAYS WITH TER.	Y) EMERGE CONSTR
	BACKFILL DROP-OFFS THAT EXCEED 3 INCH POSTED SPEED LIMITS LESS THAN 45 MPH.	ES ON ROADWAYS WITH	Z) ACCESS
	BACKFILL WITH SUITABLE COMPACTED MATER ENGINEER, AT NO EXPENSE TO THE DEPARTM	RIAL, AS APPROVED BY THE MENT.	
	DO NOT EXCEED A DIFFERENCE OF 2 INCHES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 IN	S IN ELEVATION BETWEEN OPEN LANES NCHES. INSTALL ADVANCE WARNING	

ING

L ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE AYS PRIOR TO THE BEGINNING OF CONSTRUCTION.

NO WORK IS BEING CONDUCTED FOR A PERIOD LONGER THAN ONE REMOVE OR COVER ALL ADVANCE WORK ZONE WARNING SIGNS, AS TED BY THE ENGINEER.

DE PERMANENT SIGNING.

LL BLACK ON ORANGE "DIP" SIGNS (W8-2) AND/OR "BUMP" SIGNS) 500' IN ADVANCE OF THE UNEVEN AREA, OR AS DIRECTED BY THE EER.

E ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY IC PATTERN.

FIC CONTROL DEVICES

LANE CLOSURES ARE NOT IN EFFECT SPACE CHANNELIZING DEVICES IN WORK NO GREATER IN FEET THAN TWICE THE POSTED SPEED LIMIT (MPH) T, 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN LWAY. REFER TO STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES ONS 1130 (DRUMS), 1135 (CONES) AND 1180 (SKINNY DRUMS) FOR IONAL REQUIREMENTS.

MENT MARKINGS AND MARKERS

LL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE ADWAY AS SHOWN IN THE PAVEMENT MARKING AND SIGNING PLANS.

ONE APPLICATION OF PAINT FOR TEMPORARY TRAFFIC PATTERNS. PLACE A D APPLICATION OF PAINT SIX (6) MONTHS AFTER THE INITIAL CATION AND EVERY SIX MONTHS AS DIRECTED BY THE ENGINEER.

ROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING

E/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND RS BY THE END OF EACH DAY'S OPERATION.

ESTRIAN AND BICYCLIST SAFETY

TRIAN AND BICYCLIST SAFETY MUST BE MAINTAINED AT ALL TIMES BY ATE PROJECT LIMITS, FENCING, AND SIGNAGE.

ELLANEOUS

NFORCEMENT MAY BE USED TO MAINTAIN TRAFFIC THROUGH THE WORK AND/OR INTERSECTIONS AS DIRECTED BY THE ENGINEER.

E EVENT A TIE-IN CANNOT BE MADE IN ONE DAY'S TIME, BRING THE N AREA TO AN APPROPRIATE ROADWAY ELEVATION AS DETERMINED BY NGINEER. PLACE BLACK ON ORANGE "LOOSE GRAVEL" SIGNS (W8-7) LACK ON ORANGE "PAVEMENT ENDS" SIGNS (W8-3) 200 FT AND T RESPECTIVELY IN ADVANCE OF THE UNEVEN AREAS. USE DRUMS LINEATE THE EDGE OF ROADWAY ALONG UNPAVED AREAS.

JRB RAMP LOCATIONS SHALL BE DERIVED FROM STATIONING SHOWN VEMENT MARKING PLANS OR AS DIRECTED BY THE ENGINEER IN INATION WITH THE SIGNING AND DELINEATION UNIT.

ACTOR SHALL MAINTAIN SIDEWALK ACCESS AT ALL TIMES AS STATED IN HASING. CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE TEMPORARY ALKS (CONCRETE, ASPHALT, OR OTHER SUITABLE MATERIAL AS APPROVED E ENGINEER) AT ALL LOCATIONS WHERE THE OPEN PEDESTRIAN TRAVELWAY EEN REMOVED FOR CONSTRUCTION OPERATIONS (UTILITIES, DRAINAGE, ETC.).

ENCY VEHICLE ACCESS SHALL BE MAINTAINED THROUGH THE PROJECT RUCTION AREA FOR THE DURATION OF THE PROJECT.

S SHALL BE MAINTAINED TO ALL RESIDENCES AND BUSINESSES AT ALL TIMES.

PHASING NOTES

PHASE 1:

THE CONTRACTOR SHALL PLACE ALL TO NCDOT STANDARD DRAWING NO. 1 CONSTRUCTION IS COMPLETED.

WHILE MAINTAINING EXISTING TRAF OF 19) FOR TEMPORARY LANE CLOSU IMPROVEMENTS ALONG SR 2049 (FOR

GRADING ALONG THE SHOULDER
 INSTALL DRAINAGE
 INSTALL INSTALL CURB AND GUT
 BASE COURSE, INTERMEDIATE COURS
 OF SURFACE COURSE ALONG WIDENED

PHASE 2:

WHILE MAINTAINING EXISTING TRAFF 19) FOR TEMPORARY LANE CLOSURES

INSTALL THE FINAL 1.5 INCH L
 INSTALL 4' MONOLITHIC CONCRET

3. INSTALL FINAL THERMOPLASTIC

4. GRIND/REMOVE/ADJUST EXISTING

5. PLACE TRAFFIC ONTO FINAL PAT 6. REMOVE ALL TRAFFIC CONTROL D

ROADWAY S

THE FOLLOWING ROADWAY STANDARDS TRANSPORTATION - RALEIGH, N.C., REFERENCE HEREBY ARE CONSIDERED

STD. NO.

1101.01	WORK ZONE WARN
1101.02	TEMPORARY LANE
1101.03	TEMPORARY ROAD
1101.04	TEMPORARY SHOU
1101.05	WORK ZONE VEHI
1101.11	TRAFFIC CONTRO
1110.01	STATIONARY WOR
1110.02	PORTABLE WORK
1115.01	FLASHING ARROW
1130.01	DRUMS
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGERS
1160.01	TEMPORARY CRAS
1180.01	SKINNY - DRUMS
1205.01	PAVEMENT MARKI
1205.02	PAVEMENT MARKI
1205.03	PAVEMENT MARKI
1205.04	PAVEMENT MARKI
1205.05	PAVEMENT MARKI
1205.06	PAVEMENT MARKI
1205.07	PAVEMENT MARKI
1205.08	PAVEMENT MARKI
1205.09	PAVEMENT MARKI
1205.10	PAVEMENT MARKI
1205.11	PAVEMENT MARKI
1205.13	PAVEMENT MARKI
1264.01	OBJECT MARKERS
1264.02	OBJECT MARKERS

CITY OF RALEIGH – PLANS A Electronic Approval: This ap This approval is valid upon t Review Officer below. The C plans. Any work authorized accordance with the plans k electronic approval may not modification of this approva approval. City of Raleigh Development

<form>ADVANCE WARNING STEAK PRICE TO REGINNING YORK ACCORDING INTO JOINT STEAK PRICE TO REGINNING YORK ACCORDING INTO JOINT & USING WARNING STEAK PRICE TO REGINNING YOR ACCORDING HER AND LET AND USING WARNING START AND AND FRANCISCONDALL OF A POPULATION RESTRUCTE ONDOWN AND START AND AND FRANCISCONDALL OWNER THE PROPOSED RESTRUCTE CONTRACTOR SHALL REALT IN PLACE UNIT TTO AD DECOMPLY AND STRANDAD DRAWING NO. 1101.02 (SHEET 1 OF A STRANDAR COMBE UP TO AUT NOT ING UNITED THE PROPOSED POPULATION AND NEED STRANDAD DRAWING NO. 1101.02 (SHEET 1 OF A STRANDAR COMBE UP TO AUT NOT ING UNITED THE PROPOSED POPULATION AND NEED COMBE UP TO AUT NOT ING UNITED THE PROPOSED POPULATION AND AND READ AND READ RELECTOR PARAMENT MARKER. TO INFO ADVANCE AND STRANDAD DRAWING AND TRACTOR MARKER. TO AND AND STRANDAD DRAWING AND POPULATION AND POPULATION AND POPULATION A STRANDAR AND STRANDAD DRAWING AND POPULATION AND POPULATION AND POPULATION POPULATION AND YOUR AND DRAWING AND POPULATION AND POPULATION AND POPULATION A STRAND POPULATION AND YOUR AND DRAWING AND POPULATION AND POPUL</form>			
THIS STONE SHARKA, BUDITION THE PAIL SHARKA, BUDITION	ADVANCE WARNING SIGNS PRI 1101.01(SHEET 3 OF 3). SI FFIC AND USING NCDOT STAND URES AS NEEDED, THE CONTRA RESTVILLE ROAD) AND SR 204	OR TO BEGINNING WORK ACCORDING GNS SHALL REMAIN IN PLACE UNTIL OARD DRAWING NO. 1101.02 (SHEET 1 CTOR SHALL CONSTRUCT THE PROPOSED 5/2051 (BURLINGTON MILLS ROAD) INCLUDING:	 ▲ ▲ NCLicense #C-4445 BOL 1 T ® E N G I N E E R I N G 301 S. Main Street Kamapolis, NC 28081 980.495.2250 www.exultengineering.com
STAINDARD DRAWINGS SA SHOWN IN "ROADWAY STANDARD DRAWINGS" - N.C. DEPARTMENT DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY DITLE NING SIGNS CLOSURES D CLOSURES S CURSIN S CURSING S CURSING <td< td=""><td>FFIC AND USING NCDOT STAND SE AND USING NCDOT STAND S AS NEEDED, THE CONTRACTO LAYER OF SURFACE COURSE TE ISLAND PAVEMENT MARKINGS AND RAI G PAVEMENT MARKINGS IN CON TTERN. DEVICES AND SIGNAGE.</td><td>PAIH, SIGNAL MODIFICATION, ASPHALT TO BUT NOT INCLUDING THE FINAL 1.5" PARD DRAWING NO. 1101.02 (SHEET 1 OF TR SHALL: SED REFLECTIVE PAVEMENT MARKERS. IFLICT WITH PROPOSED.</td><td>PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA</td></td<>	FFIC AND USING NCDOT STAND SE AND USING NCDOT STAND S AS NEEDED, THE CONTRACTO LAYER OF SURFACE COURSE TE ISLAND PAVEMENT MARKINGS AND RAI G PAVEMENT MARKINGS IN CON TTERN. DEVICES AND SIGNAGE.	PAIH, SIGNAL MODIFICATION, ASPHALT TO BUT NOT INCLUDING THE FINAL 1.5" PARD DRAWING NO. 1101.02 (SHEET 1 OF TR SHALL: SED REFLECTIVE PAVEMENT MARKERS. IFLICT WITH PROPOSED.	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
SH CUSHION S INGS - LINE TYPES AND OFFSETS INGS - LINE TYPES AND OFFSETS INGS - EXITS AND ENTRANCE RAMPS INGS - EXITS AND ENTRANCE RAMPS INGS - EXITS AND ENTRANCE RAMPS INGS - INTERSECTIONS INGS - TURN LANES INGS - TURN LANES INGS - PEDESTRIAN CROSSWALKS INGS - PEDESTRIAN CROSSWALKS INGS - PAINTED ISLANDS INGS - RAILROAD CROSSINGS INGS - LANE REDUCTIONS S - TYPES S - TYPES S - INSTALLATION AUTHORIZED FOR CONSTRUCTION approval is being issued electronically. It mesignature of a City of Raleign city will retain a copy of the approved is being issued electronically. It mesignature of a City of Raleign city will retain a copy of the approved is othe celted once issued. Any will once issued will invalidate this ent Approval: iter	S AS SHOWN IN "ROADWAY STA , DATED JANUARY 2024 ARE A D A PART OF THESE PLANS: TITLE NING SIGNS E CLOSURES D CLOSURES ULDER CLOSURES ICLE ACCESSES OL DESIGN TABLES RK ZONE SIGNS W BOARDS	DRAWINGS" - N.C. DEPARTMENT PPLICABLE TO THIS PROJECT AND BY	TRAFFIC MANAGEMENT PLAN
These plans have been electronically approved for construction approval is being issued electronically. the signature of a City of Raleigh City will retain a copy of the approved active will retain a copy of the approved by this approval must proceed in skept on file with the City. This note edited once issued. Any val once issued will invalidate this ent Approval: icer These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued. Planning Banning	SH CUSHION S INGS - LINE TYPES AND OFFS INGS - TWO LANE AND MULTIL INGS - EXITS AND ENTRANCE INGS - INTERSECTIONS INGS - INTERSECTIONS INGS - LANE DROPS INGS - PEDESTRIAN CROSSWAL INGS - PEDESTRIAN CROSSWAL INGS - PAINTED ISLANDS INGS - SCHOOL AREAS INGS - RAILROAD CROSSINGS INGS - LANE REDUCTIONS S - TYPES S - INSTALLATION	SETS ANE ROADWAYS RAMPS .KS SSAGES TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX	SEAL PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION SIGNATURE DATE DATE DATE
	AUTHORIZED FOR CONSTRUCTION approval is being issued electronically. In the signature of a City of Raleigh e City will retain a copy of the approved of by this approval must proceed in skept on file with the City. This ot be edited once issued. Any val once issued will invalidate this ent Approval:	These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued. Planning	JOB NO:: 00103002 DATE: 10/23/24 SCALE: 1" = 50' REVISIONS PHEET NO'
			Ŭ



CITY OF RALEIGH - PLAN	S/
Electronic Approval: This This approval is valid upo	ap on t
Review Officer below. The plans. Any work authorize	ne i
accordance with the plan electronic approval may modification of this appr approval.	no no ov
City of Raleigh Developn	ner





















4 Roadway/00103002 Pearce Farm Roadway and SignalDesign/10 CAD/Roadway/Proj/Pearce Farm_rdy_20_psh_R-4.dgn	INCIDENT AL MILLING ROADWAY WIDENING/ FULL-DEPTH PAVEMENT WILL AND OVERLAY CONCRETE NOTES: IRADNI DIMENSIONS ARE TO THE EDGE OF PAVEWENT UNLESS OTHERMISE NOTED	DETAIL 1 SPECIAL LATERAL 'N' DITCH (Not to Socie)	SITIONAS MARSHALL TRUSTEES BM.2001 PG.454 TO R.2001 TRUSTEES BM.2001 PG.454 TO R.2001 TRUSTEES THOMAS MARSHALL TRUSTEES BM.2011 PG.454 TO R.2011 TRUSTEES
10/25/2024 Z:\Shared\O Projects_4	PAVEMENT UNLESS OTHERWISE NOTED (APPLIES TO ALL SHEETS). 2.CROSS SLOPES VARY ALONG -L3- IN SHOULDER SECTIONS. REFER TO TYPICAL TYPICAL SECTION AND CROSS SECTIONS. 3.UNLESS OTEHRWISE NOTED DRIVEWAY MATERIAL WILL BE ASPHALT WITH IO' TURNING RADII. ASPHALT DRIVEWAYS SHALL BE 2" S9.5C ON 8" AGGREGATE BASE COURSE. 4.RELOCATE EXISTING COMMUNICATION AND FIBER OPTIC UTILITY LINES OUTSIDE THE LIMITS OF THE PROPOSED WIDENING.	$\frac{\text{Natural Ground}}{\text{Ground}} \stackrel{\text{S.}}{} \frac{\text{D}}{\text{Fill Slope}} \\ \text{Min. D} = 1 \text{ Ft.} \\ \text{FROM } -\text{L3} - \text{ STA. 14} + 15 \text{ TO } \text{ STA. 15} + 25 \text{ LT} $	









310							
310							
300							
290							
280						END OVERLAY	
			BE	GIN CONSTRUCTION BEGIN OVERLA		BEGIN OVERLAY -L1- STA. 13 + 60.0 ELEV = 253.10'	& WE 00
270			EL	-L1- STA. 13 + 10.00 EV = 251.92' (EXIST	D)	PI =	= 14+
						VC K =	= 25 = 10 = 139
260							
250						(+)3.5474%	
230 -					(+1724%		
240			EXISTING	G GROUND -		BEGIN	SPECH
				BEGIN SPECIAL		DITCH -U-S ELEV =	<u>GRADE</u> TA 14+ = 250.9
230				-U- STA 13+05 ELEV = 248.25'			
				END DITCI -LI- ELEV	SPECIAL <u>H GRADE LT</u> STA 13+35 ' = 250.63'		
220		11	12	1;	3	14	



WEDGING N OVERLAY A. 21+33.00 = 281.49'	END CONSTRUCTION END OVERLAY -L1- STA. 22 + 95.00 ELEV = 289.54' (EXIST)	310	Image: Construction of the construc
+83.00 79.06' 0'		290	MENTS AROLINA
(+)4.8570% (+)6.33%	END SPECIAL	280	FARM PROVE/ RTH C/
BEGIN SPECIAL <u>DITCH GRADE RT</u> -LI- STA 21+60 ELEV = 279.80' BEGIN SPECIAL <u>DITCH GRADE LT</u>	END SPECIAL DITCH GRADE RT	260	PEARCE WAY IM ILLE, NO
-LI- STA 22+00 ELEV = 283.98'	-U- STA 22+50 ELEV = 285.50'	250	ROAE ROLESV
		240	
21 2:	2 23	220	SHEET
			PROFILE
			SEAL NORTH CAROL NORTH CAROL NORTH CAROL NOFESSION SEAL DO NOT USE FOR CONSTRUCTION NGINEER NGINER NGINAR NGINER NGINER NGINAR NGINAR NGINER NGINAR NGINAR NG
	50 25 0 50 100 PROFILE (HORIZONTAL) 10 5 0 10 20 PROFILE (VERTICAL)		JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 10/23/24 REVIEWED BY: E. LYNCH SCALE: 1" = 50' INIT. REVISIONS INIT. DATE
			SHEET NO.





			Ê
		380	E E R I N G Aain Street is, NC 28081 95.2250 ngineering.com
	END OVERLAY -L4- STA. 23 + 32.00 ELEV = 348.60' (EXIST)	370	E N G I N 801.5. N 880.4 www.exulte
		360	NC License #C-4445
		a 350	TS
		340	M TEMEN CARO
		330	E FAR APROV ORTH
BEGIN SPECIAL <u>DITCH GRADE LT</u> -L4- STA 21+50 ELEV = 342.07'		320	PEARC VAY IN LE, NO
		310	ROADV
		300	0 0
		290	
21	22 22		HEET
			Ш С
		370	ROFIL
		360	
		360	SEAL
		360 350 340	SEAL NORTH CAROLINA NORTESSION ROFESSION SEAL
		360 350 340 330	SEAL ORTH CAROLINA ORTH CAROLINA SEAL DO NOT USE FOR CONSTRUCTION MGINEER MBETH W. LANS
		360 350 340 330 330	SEAL SEAL SEAL SEAL DRELIMENTARY PLANS DO NOT USE FOR CONSTRUCTION SIGNATURE DATE HONON DATE HONON DATE
			CONTENTION OF LOSS IN THE CAROL IN THE CAROL IN THE CAROL IN THE SEAL OF LOSS IN THE SEAL OF LOSS IN THE SEAL OF LOSS IN THE OF LOSS INTERVITIES INTO THE OF LOSS INTO THE OF L
	50 25 0 50 PROFILE (HORIZONTA		3002 DESIGNED BY: G. BOYLE SEAT BUD NOL REFUNCTION SIGNATORE S
	50 25 0 50 50 25 0 50 PROFILE (HORIZONTA 10 5 0 10 PROFILE (VERTICAL)		OB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. S. 10/1/4 BEDI NOL: 0010302 SEAT DATE DATE: 102324 Reviewed By: E. LYNCH SEAT DATE DATE SIGNATURE DATE DATE SIGNATURE DATE DATE SIGNATURE DATE DATE
	50 25 0 50 FROFILE (HORIZONTA 10 5 0 10 PROFILE (VERTICAL) 35		SEAL CAROLINA RELIMENTIARY PLANS SEAL PRELIMENTARY PLANS NGINEFR NGINEFR NGINEFR NGINEFR NGINEFR NGINEFR NGINEFR NGINE SIGNATURE DATE DA



390					
380					
370					
360	8	PI = 4I + 8	30.00		
	42+0	EL = 34	4.57' Y		PROPOS
350	TA - R-III	K = 77			
		(+)0.6	5344%		
	-T2				(+)0.63442
340					
	(SL CHL				
330	MAT				
320					
		42	43	4	. <u>4</u>
		12	43	4	. <u>.</u>
		12	43	4	.4
		12	43	4	.4
		12	43	4	.4
		42	43	4	
			43		
			43		
			43		
















NOTE:

NOTE:

PERIMETER EROSION CONTROL MEASURES SHALL BE INSTALLED DURING CLEARING AND GRUBBING PHASE.

PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE – B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

























CONSTRUCTION NARRATIVE

PROJECT DESCRIPTION

The proposed Pearce Farm roadway improvements are located along Forestville Road (SR 2049) and Burlington Mills Road (SR 2045/SR 2051) in Rolesville and Wake Forest, North Carolina. The project includes a site driveway along Forestville Rd with the improvements at the site driveway, 3 site driveways along Burlington Mills Rd with frontage widening and improvements at each site driveway and intersection improvements at Forestville Rd and Burlington Mills Rd. The existing roadway has an existing shoulder section with roadside ditches and that typical section will remain the same for portions of the widening beyond the site frontage. A curb and gutter section will be constructed along the site frontage and in areas where the right of way and easements will be minimized.

The site is generally flat and contains some drainage ways that are bordered by moderate slopes. Land use along the roadways is commerical and residential. The drainage from this site makes its way through a series of roadside ditches and cross pipes and mostly drains to Tom's Creek with the exception of a portion of the drainage north of Burlingon Mills Road that drains to Sanford Creek. The soil types within the project limits are primarily sandy loams (RaB, RaC, and WfB).

The total disturbed area is approximately 8.1 acres.

CONSTRUCTION SEQUENCE

CONSTRUCTION SPECIFICATIONS

1. Request preconstruction meeting with the Environmental Consultant. Hold preconstruction meeting at least one week prior to starting construction and invite a representative from NCDEMLR LQS, contact number is (919) 791–4200.

2. No land disturbing activities, including timbering or demolition activities, are allowed without first obtaining a sediment and erosion control plan approval and Certificate of Coverage.

3. Erosion and Sediment Control (E&SC) permit and a Certificate of Coverage (COC) must be obtained before any land disturbing activities (including timbering and demolition) occur.

4. Flag the work limits and mark the trees to remain and buffer area for protection.

5. Per NPDES requirements, a rain gauge, self-inspections records, permit, Certificate of Coverage, and S&E plan are required to be maintained on site and accessible during inspection. It is recommended that these items be placed in a permits box at the beginning or entrance of project.

6. Install erosion control measures as shown on the approved plan including, but not limited to gravel construction pad, silt fence, inlet protection, and check dams. Clear only as necessary to install these devices. Seed temporary diversions, berms and basins immediately after installation.

7. Stockpiles, laydown or waste areas, concrete washouts, portable toilets, and fuels must be located at least 50 feet away from any open water conveyances, such as basins, ditches, storm drain inlets, etc. The location of these activities may be field adjusted if the distance requirements are met.

8. Call Environmental Consultant for an onsite inspection by the Environmental Consultant to obtain a Certificate of Compliance.

9. Begin clearing and grubbing. Maintain devices as needed. Rough grade site.

10. Per the NPDES Permit, ground stabilization will be applied within 14 calendar days from last land disturbing activity. For steep slopes, that area must be stabilized within 7 calendar davs.

11. Install storm sewer, if shown, and protect inlets with inlet protection devices, wattles, or other approved measures as shown on the plan.

12. If dewatering is required, it is to be done through silt bags with a floating intake that is constantly monitored while in use.

13. Begin construction and stabilize site as areas are brought up to finish grade with vegetation, paving, erosion control matting, etc. Seed and mulch denuded areas per Ground Stabilization Time Frames.

14. When construction is complete and all areas are stabilized completely, call Environmental Consultant for an inspection.

15. After site is approved, remove temporary diversions, silt fence, inlet protection, etc., and seed out or stabilize any resulting bare areas. All remaining permanent erosion control devices, such as velocity dissipators, should now be installed.

16. When vegetation has become established, call for a final site inspection by the Environmental Consultant. Obtain a Certificate of Completion.

17. When the project is complete, the permittee shall contact DEMLR to close out the E&SC Plan.

18. Estimated time for before final stabilization – 14 months.

MAINTENANCE

Follow the construction sequence throughout project development. Adequate erosion and sediment control devices shall be in place and adjusted as needed based on the clearing & grubbing, construction, and permanent vegetation phases. All devices shall be maintained in accordance with the devices specific maintenance requirements and remain in place until permanent vegeation on the project is established and a Certificate of Completion is obtained.

Notification of Land Resources Sediment and Erosion Control Self-Inspection Program:

The self-inspection program is separate from the weekly self-monitoring program of the NPDES Stormwater Permit for Construction Activities. The focus of the self-inspection report is the installation and maintenance of erosion and sedimentation control measures according to the approved plan. The inspections must be conducted after each phase of the project and continue until permanent ground cover is established in accordance with NCGS 113A-54.1 and 15A NCAC 4B.0131.

The self-inspection Report form is available from https://deg.nc.gov/about/divisions/energy_mineral_land_resources/erosion_sediment_control/forms.

If you have questions or cannot access the form, please contact NCDEMLR Divsion of Energy, Mineral and Land Resources at (919)791–4200.

2024 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch – N. C. Department of Transportation – Raleigh, N. C. Dated January, 2024 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
1605.01	Temporary Silt Fence
1606.01	Special Sediment Control Fence
1607.01	Gravel Construction Entrance
1622.01	Guide for Temporary Berms and Slope Drains
1630.03	Temporary Silt Ditch
1630.05	Temporary Diversion
1630.06	Special Stilling Basin
1631.01	Matting Installation
1632.01	Rock Inlet Sediment Trap Type A
1632.02	Rock Inlet Sediment Trap Type B
1632.03	Rock Inlet Sediment Trap Type C
1633.01	Temporary Rock Silt Check Type A
1633.02	Temporary Rock Silt Check Type B
1635.01	Rock Pipe Inlet Sediment Trap Type A
1635.02	Rock Pipe Inlet Sediment Trap Type B
1636.01	Wattle Check
1640.01	Coir Fiber Baffle
1645.01	Temporary Stream Crossing

EROSION CONTROL NOTES

1. All construction activities are requried to follow the NCG01 Permit Issued by NCDEQ. Refer to sheet EC-17 and EC-18.

2. Before beginning work, the contractor is required to meet with the town at the site to review all work procedures, access routes, storage areas, and tree protection measures.

3. Temporary fences and/or silt fence should be erected to protect trees to be preserved. Fences define a specific protection zone for each tree or group of trees. Fences are to remain until all site work has been completed. Fences may not be relocated or removed without the written permission of the town.

4. Control sediment on site and prevent from washing onto adjacent roadways. Provide inlet protection at inlets throughout construction and silt fencing or NCDOT #57 stone piled 1' high by 2' wide at base as applicable to prevent sediment from leaving the sites or entering adjacent storm drainage systems. All erosion control measures shall be installed per the local municipality standard details or 2024 NCDOT roadway standard drawings as noted on the plans. Maintenance of erosion control measures is incidental to erosion control.

5. At the start of grading involving the lowering of the existing grade around a tree or stripping of topsoil, a clean, sharp, vertical cut shall be made at the edge of the tree save area at the same time as other erosion control measures are installed.

6. No storage of materials, dumping of waste materials, fill, or parking of equipment/vehicles shall be allowed within the tree protection zone.

7. If existing trees to be retained are damaged or destroyed, the contractor shall replace tree matching existing species and size at no additional cost to the owner. If injury should occur to any tree during construction, it should be evaluated as soon as possible by the town so that appropriate treatments can be applied. Any roots damaged during grading or construction shall be exposed to sound tissue and cut cleanly with a saw.

8. Additional tree pruning required for clearance during construction must be performed by a gualified arborist and not by construction personnel. (incidental to other items in the contract)

9. All underground utilities and drain lines shall be routed outside of the tree protection zone. If lines must traverse the protection area, they shall be tunneled or bored under the tree.

10. Any herbicides placed under paving materials must be safe for use around trees and labeled for that use. Any pesticides used on site must be tree-safe and not easily transported by water.

11. If temporary haul or access roads must pass over the root area of trees to be retained, a road bed of 6 inches of mulch or gravel shall be created to protect the soil. The road bed material shall be replenished as necessary to maintain a 6-inch depth.

MAINTENANCE PLAN

1. The contractor shall install and maintain a rain gauge in good working order on site at all times. Additionally, the Contractor is responsible for inspecting all erosion and sediment control practices for stability and operation following every runoff-producing rainfall (1/2" or greater in a 24-hr period), but in no case less than once every week. Both the rain gauge and inspection/maintenance of practices shall be maintained in accordance with the NCG01 Self-Inspection requirements, shown on page EC-6.

2. The contractor shall remove sediment from sediment basin, sediment traps, and gravel inlet protection devices when storage capacity has been approximately 50% filled. Gravel will be cleaned or replaced when the sediment pool no longer drains properly.

3. The contractor shall remove sediment from behind silt fence when it becomes 0.5 feet deep at the fence. Silt fence will be repaired as necessary to maintain a barrier.

4. The contractor shall fertilize, reseed, as necessary and mulch according to specifications in the vegetative plan to maintain a vigorous, dense, vegetative cover.

5. The contractor must inspect outlets where stormwater runoff leaves the site and evaluate the effect on nearby streams or wetlands. Corrective action must be taken if sediment is deposited off sife or into stream or wetlands, or causes a visible increase in turbidity of any water body.

ل ں Main Street blis, NC 28081 495.2250 \square $\mathbf{X}_{\mathbf{0}}^{-}$ PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA **ONTROL DETAILS** EROSION CON NOTES AND

6. The contractor shall provide ground cover on exposed slopes or other areas within the timeframes specified in the stabilization table or sooner of completion of any phase of aradina. 7. Contact Brian Ketchem at 919–724–0624 should erosion and sediment control issues arise during land-disturbing activity. 8. The following are specific maintenance requirements for each proposed erosion and sedimentation control device: STANDARD TEMPORARY SILT FENCE/STANDARD SILT FENCE OUTLET/J-HOOKS: Inspect sediment fences and fence outlets at least once a week and after each rainfall. Make any required repairs immediately. Should the fabric of a sediment fence collapse, tear, decompose or become ineffective, replace it promptly. Remove sediment deposits as necessary to provide adequate storage volume for the next rain and to reduce pressure on the fence. Take care to avoid undermining the fence during cleanout. Remove all fencing materials and unstable sediment deposits and bring the area to grade and stabilize it after the contributing drainage area has been properly stabilized. STANDARD CATCH BASIN/YARD INLET PROTECTION: Inspect inlets at least weekly and after each significant (one-half inch or greater rainfall event.) Clear the mesh wire of any debris or other objects to provide adequate flow for subsequent rains. Take care not to damage or undercut the wire mesh during sediment removal. Replace stone as needed. STANDARD INLET SEDIMENT CONTROL DEVICE: Inspect sediment sack weekly and after each significatn rainfall event (1/2 inch or greater) Remove accumulated sediment and any debris. The sediment sack must be replaced if clogged or torn. If ponding becomes excessive, the sediment sack shall may need to be checked daily and replaced more frequently. The sediment sack shall be inspected until land disturbance is complete and teh area above the measure has been permanently stabilized. OUTLET STABILIZATION STRUCTURE: Inspect riprap outlet structures weekly and after significant (1/2 or greater) rainfall events to see if any erosion around or below the riprap has taken place or if stones have been dislodged. Immédiantly make all needed repairs to prevent further damage. TREE PROTECTION FENCE: Inspect tree protection fences at least once a week and after each rainfall. Make any required repairs immediately. Should the fabric of a tree protection fence collapse, tear, decompose or become ineffective, replace it promptly. STANDARD CONSTRUCTION ENTRANCE: Maintain the stone pad in a condition to prevent mud or sediment from leaving the construction site. This may require periodic topdressing with 2-inch stone. After each rainfall, inspect any structure used to trap sediment and clean it out as necessary. Immediately remove all objectionable materials spilled, washed, or tracked onto public roadways. TEMPORARY ROCK SILT CHECK DAMS. TYPE A AND B: Inspect check dams and channels at least weekly and after each significant (1/2 inch or greater) rainfall event and repair immediately. Clean out sediment, straw, limbs, or other debris that could clog the channel when needed. Anticipate submergence and deposition above the check dam and erosion from high flows around the edges of the dam. Correct all damage immediately. If significant erosion occurs between dams, additional measures can be taken such as, installing a protective riprap liner in that portion of the channel (Practice 6.31, Riprap–lined and Paved Channels.) Remove sediment accumulated behind the dams as needed to prevent damage to channel vegetation, allow the channel to drain through the stone check dam, and prevent large glows from carrying sediment over the dam. Add stones to dams as needed to maintain design height and cross section. SPECIAL STILLING BASIN (SEDIMENT FILTER BAG WITH GRAVEL PAD): The special stilling basin shall be disposed of and replaced when it is $\frac{3}{4}$ full of sediment or when it is impractical for the bag to filter the sediment out at a reasonable flow rate. The inlet of the bag should be inspected periodically for damage and/or blockage. The float intake shall be constantly monitored while in use. Sediment control stone shall be replaced if damaged by high flows or bag failure. WATTLES (COMPOST SOCK):

Inspect wattles weekly and after each significant rainfall event (1/2 inch or greater). Remove accumulated sediment and any debris. The watte must be replaced if clogged or torn. If ponding becomes excessive, the wattle may need to be replaced with a larger diameter or different measure. The wattle needs to be reinstalled if undermined or dislodged. The wattler shall be inspected until land disturbance is complete and the area above the measure has been permanently stabilized.

GROUNDWATER DEWATERING: The pump shall be monitored 24/7 until construction activity is complete.

CONCRETE WASHOUT: Inspect after each significant rainfall event. Stormwater acumulated within the washout may not be pumped into or discharged to the storm drainage system or receiving waters. Liquid waste musth be pumped out and removed from the project. Remove leavings from the washout when at approximately 75% capacity to limit overflow events. Replace the tarp, sand bags or other temporary structure components when no longer functional.

CITY OF RALEIGH - PLANS AUTHORIZED FOR CONSTRUCTION Electronic Approval: This approval is being issued electronically. This approval is valid upon the signature of a City of Raleigh Review Officer below. The City will retain a copy of the approved plans. Any work authorized by this approval must proceed in accordance with the plans kept on file with the City. This electronic approval may not be edited once issued. Any

modification of this approval once issued will invalidate this approval.

City of Raleigh Development Approval:

Raleigh Water Review Officer

TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX

SEAL

CARO

ROFESSIONA

DRELIMINARY PLANS

ABETH W. LYNN

JC DATE: SCALE: REVISIO

SHEET NO.

EC-15

These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued.

Public Works/Engineering

These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued.

Planning

LAND GRADING (NCDENR 6.02)

CONSTRUCTION SPECIFICATIONS

1. Construct and maintain all erosion and sedimentation control practices and measures in accordance with the approved sedimentation control plan and construction schedule.

2. Remove good topsoil from areas to be graded and filled, and preserve it for use in finishing the grading of all critical areas.

3. Scarify areas to be topsoiled to a minimum depth of 2 inches before placing topsoil (Practice 6.04, Topsoiling).

4. Clear and grub areas to be filled by removing trees, vegetation, roots, or other objectionable material that would affect the planned stability of the fill.

5. Ensure that fill material is free of brush, rubbish, rocks, logs, stumps, building debris, and other materials inappropriate for constructing stable fills.

6. Place all fill in layers not to exceed 9 inches in thickness, and compact the layers as required to reduce erosion, slippage, settlement, or other related problems.

7. Do not incorporate frozen, soft, mucky, or highly compressible materials into fill slopes.

8. Do not place fill on a frozen foundation, due to possible subsidence and slippage.

9. Keep diversions and other water conveyance measures free of sediment during all phases of development.

10. Handle seeps or springs encountered during construction in accordance with approved methods (Practice 6.81, Subsurface Drain).

11. Permanently stabilize all graded areas immediately after final grading is completed on each area in the grading plan. Apply temporary stabilization measures on all graded areas when work is to be interrupted or delayed for 30 working days or longer.

12. Show topsoil stockpiles, borrow areas, and spoil areas on the plans, and make sure they are adequately protected from erosion. Include final stabilization of these areas in the plan

MAINTENANCE Periodically, check all graded areas and the supporting erosion and sedimentation control practices, especially after heavy rainfalls. Promptly remove all sediment from diversions and other water-disposal practices. If washouts or breaks occur, repair them immediately. Prompt maintenance of small eroded areas before they become significant gullies is an essential part of an effective erosion and sedimentation control plan.

TOPSOILING (NCDENR 6.04)

CONSTRUCTION SPECIFICATIONS

MATERIALS

Determine whether the quality and quantity of available topsoil justifies selective handling. Quality topsoil has the following characteristics:

Texture – loam, sandy loam, and silt loam are best; sandy clay loam, silty clay loam, clay loam, and loamy sand are fair. Do not use heavy clay and organic soils such as peat or muck as topsoil

Organic matter content – (sometimes referred to as "humic matter") should be greater than 1.5% by weight.

Acidity – pH should be greater than 3.6 before liming, and liming is required if it is less than 6.0.

Soluble salts – should be less than 500 ppm.

Sodium – sodium adsorption ratio should be less than 12. The depth of material meeting the above qualifications should be at least 2 inches. Soil factors such as rock fragments, slope, depth to water table, and layer thickness affect the ease of excavation and spreading of topsoil. Generally, the upper part of the soil, which is richest in organic matter, is most desirable; however, material excavated from deeper layers may be worth storing if it meets the other criteria listed above. Organic soils such as mucks and peats do not make good topsoil. They can be identified by their extremely light weight when dry.

TOPSOILING (NCDENR 6.04)

STRIPPING

Strip topsoil only from those areas that will be disturbed by excavation, filling, roadbuilding, or compaction by equipment. A 4-6 inch stripping depth is common, but depth varies depending on the site. Determine depth of stripping by taking soil cores at several locations within each area to be stripped. Topsoil depth generally varies along a gradient from hilltop to toe of the slope. Put sediment basins, diversions, and other controls into place before stripping.

STOCKPILING

Select stockpile location to avoid slopes, natural drainageways, and traffic routes. On large sites, respreading is easier and more economical when topsoil is stockpiled in small piles located near areas where they will be used.

Sediment barriers – Use sediment fences or other barriers where necessary to retain sediment.

Temporary seeding – Protect topsoil stockpiles by temporarily seeding as soon as possible, no more than 21 calendar days after the formation of the stockpile (Practice 6.10, Temporary Seeding).

Permanent vegetation – If stockpiles will not be used within 90 days they must be stabilized with permanent vegetation to control erosion and weed growth (Practice 6.11, Permanent Seeding).

SITE PREPARATION

Before spreading topsoil, establish erosion and sedimentation control practices such as diversions, berms, dikes, waterways, and sediment basins.

Grading – Maintain grades on the areas to be topsoiled according to the approved plan and do not alter them by adding topsoil.

Limit of subsoil – Where the pH of the existing subsoil is 6.0 or less, or the soil is composed of heavy clays, incorporate agricultural limestone in amounts recommended by soil tests or specified for the seeding mixture to be used (Practice 6.11, Permanent Seeding). Incorporate lime to a depth of at least 2 inches by disking.

spreading topsoil.

SPREADING TOPSOIL Uniformly distribute topsoil to a minimum compacted depth of 2 inches on 3:1 slopes and 4 inches on flatter slopes. To determine the volume of topsoil required for application to various depths, use Table 6.04a. Do not spread topsoil while it is frozen or muddy or when the subgrade is wet or frozen. Correct any irregularities in the surface that result from topsoiling or other operations to prevent the formation of depressions or water pockets.

Compact the topsoil enough to ensure good contact with the underlying soil, but avoid excessive compaction, as it increases runoff and inhibits seed germination. Light packing with a roller is recommended where high-maintenance turf is to be established.

On slopes and areas that will not be mowed, the surface may be left rough after spreading topsoil. A disk may be used to promote bonding at the interface between the topsoil and subsoil

After topsoil application, follow procedures for seedbed preparation, taking care to avoid excessive mixing of topsoil into the subsoil

TEMPORARY SEEDBED PREPARATION 1. Seedbed preparation is essential to successful plant establishment. A good seedbed is well-pulverized, loose, and uniform. In areas to be planted, soil shall be tilled to a 6-inch depth and all loose rocks, roots and other obstructions should be removed

4. Evenly apply seed mix given in table using a cyclone seeder, drill, or cultipacker seeder. Use seed rates give in table. Small grains should be planted no more than 1 inch deep, and grasses and legumes no more than 1/2 inch. Broadcast seed must be coverd by racking or chain dragging, and then lightly firmed with a rooler or cultipacker.

5. Mulch immediately after seeding with small grain straw at a rate of 4,000 lbs per acre. Anchor mulch with asphalt emulsion at 400 gals/acre.

6. Inspect seeded areas and make repairs as needed or reseed within the planting season, if possible.

MARC MARC MARC MARC MARC JUN SEPT NOV

AUG NOV MARC MARC

JULY

WHERE LIMITS OF DISTURBANCE ARE ADJACENT TO EXISTING TURFGRASS AREAS, CONTRACTOR SHALL PROVIDE A PERMANENT SEED BLEND OF TALL FESCUE AND KENTUCKY BLUEGRASS OR ANOTHER SEED MIXTURE AS DIRECTED BY THE OWNER. PROVIDE SOIL AMENDMENTS IN SEEDED AREAS BASED ON SOIL TEST REPORT AND PER SPECIFICATIONS.

WHERE LIMITS OF DISTURBED AREA ARE ADJACENT TO EXISTING FOREST FLOOR/UNDER COVER (NO TURFGRASS PRESENT), CONTRACTOR SHALL PROVIDE HARDWOOD MULCH (4" DEPTH) OUTSIDE OF THE SHOULDER OF THE TRAIL.

FOR PERMANENT SEED, CONTRACTOR SHALL UTILIZE SEED THAT MATCHES THE EXISITING CONDITIONS. REFER TO THE PROJECT SPECIAL PROVISIONS.

TOPSOILING (NCDENR 6.04) CONTINUED

SITE PREPORATION CONTINUED

Roughening – Immediately prior to spreading the topsoil, loosen the subgrade by disking or scarifying to a depth of at least 4 inches, to ensure bonding of the topsoil and subsoil. If no amendments have been incorporated, loosen the soil to a depth of at least 6 inches before

TEMPORARY SEEDING (NCDENR 6.10) & PERMANENT SEEDING (NCDENR 6.11)

2. Apply agricultural limestone uniformly at a rate of 2–3 tons/acre or accordinat to soil test recommendations. Apply a 10–10–10 grade fertilizer at 700–1,000 lb/acre. Both fertilizer and lime should be incorporate into the top 4-6 inches of soil.

3. If recent tillage operations have resulted in a loose surface, additional roughening may not be required, except to break up large clods. If rainfall causes the surface to become sealed or crusted, lossen it just prior to seeding by disking, racking, harrowing, or other suitable methods.

	SHOULDERS, SIDE DITCHES, SLOPES (FOR SLOPES BETWEEN 2:1 AND 3:1)	
DATE	ТҮРЕ	PLANTING RATE
CH 1 – JUNE 1	CENTIPEDEGRASS	10–20 LB/ACRE (SEED) 33 BU/ACRE (SPRIGS)
CH 1 – JUNE 1	PANICUM VIRGATUM (SWITCHGRASS) AND	50 LBS/ACRE
CH 1 – APRIL 15	ADD TALL FESCUE OR	250 LBS/ACRE
CH 1 – JUNE 30	ADD WEEPING LOVEGRASS OR	10 LBS/ACRE
CH 1 – JUNE 30	ADD HULLED COMMON BERMUDAGRASS	25 LBS/ACRE
NE 1 – SEPT 1	*TALL FESCUE <u>AND</u> *BROWNTOP MILLET <u>OR</u> *SORGHUM–SUDAN HYBRIDS	250 LBS/ACRE 35 LBS/ACRE 30 LBS/ACRE
1 – MARCH 1	PANICUM VIRGATUM (SWITCHGRASS) AND TALL FESCUE	70 LBS/ACRE 120 LBS/ACRE
1 – MARCH 1	ADD ABRUZZI RYE	25 LBS/ACRE

SHOULDERS, SIDE DITCHES, SLOPES (FOR SLOPES 3:1 AND FLATTER)

DATE	TYPE	PLANTING RATE
AUG 15 – NOV 1	TALL FESCUE	300 LBS/ACRE
NOV 1 – MARCH 1	TALL FESCUE AND ABRUZZI RYE	300 LBS/ACRE
MARCH 1 – APRIL 15	TALL FESCUE	300 LBS/ACRE
MARCH 1 – JUNE 1	CENTIPEDEGRASS	10–20 LB/ACRE (SEED) 33 BU/ACRE (SPRIGS)
APRIL 15 – JUNE 30	HULLED COMMON BERMUDAGRASS	25 LBS/ACRE
JULY 15 – AUG 15	TALL FESCUE AND *BROWNTOP MILLET OR *SORGHUM-SUDAN HYBRIDS	35 LBS/ACRE

PERMANENT SEEDING SCHEDULE

PERMANENT SEEDING OF RIPARIAN & WETLAND AREAS		
SPECIES	COMMON NAME	PERCENT
ELYMUS VIRGINICUS	VIRGINIA WILD RYE	20
AGROSTIS PERENNANS	AUTUMN BENTGRASS	15
PANICUM VIRGATUM	SWITCHGRASS	15
RUDBECKIA HIRTA	BLACK-EYED SUSAN	10
COREOPSIS LANCEOLATA	LANCELEAF COREOPSIS	10
ANDROPOGON GERARDII	BIG BLUESTEM	10
JUNCUS EFFUSUS	SOFT RUSH	5
SCHIZACHYRIUM SCOPARIUM	LITTLE BLUESTEM	5
SORGHASTRUM NUTANS	INDIAN GRASS	5
TRIPSACUM DACTYLOIDES	EASTERN GAMMA	5
		100

PERCENTAGES ARE BY WEIGHT OF PURE LIVE SEED (PLS)

RIP RAP (NCDENR 6.15)

CONSTRUCTION SPECIFICATIONS

Subgrade preparation – Prepare the subgrade for riprap and filter to the required lines and grades shown on the plans. Compact any fill required in the subgrade to a density approximating that of the surrounding undisturbed material or overfill depressions with riprap. Remove brush, trees, stumps, and other objectionable material. Cut the subgrade sufficiently deep that the finished grade of the riprap will be at the elevation of the surrounding area. Channels should be excavated sufficiently to allow placement of the riprap in a manner such that the finished inside dimensions and grade of the riprap meet design specifications.

Sand and gravel filter blanket – Place the filter blanket immediately after the ground foundation is prepared. For gravel, spread filter stone in a uniform layer to the specified depth. Where more than one layer of filter material is used, spread the layers with minimal mixing.

Synthetic filter fabric – Place the cloth filter directly on the prepared foundation. Overlap the edges by at least 12 inches, and space anchor pins every 3 ft along the overlap. Bury the upstream end of the cloth a minimum of 12 inches below ground and where necessary, bury the lower end of the cloth or over lap with the next section as required.

Take care not to damage the cloth when placing riprap. If damage occurs remove the riprap, and repair the sheet by adding another layer of filter material with a minimum overlap of 12 inches around the damaged area. If extensive damage is suspected, remove and replace the entire sheet.

Where large stones are used or machine placement is difficult, a 4-inch layer of fine gravel or sand may be needed to protect the filter cloth.

Stone placement – Placement of riprap should follow immediately after placement of the filter. Place riprap so that it forms a dense, well-graded mass of stone with a minimum of voids. The desired distribution of stones throughout the mass may be obtained by selective loading at the guarry, and controlled dumping during final placement. Place riprap to its full thickness in one operation. Do not place riprap by dumping through chutes or other methods that cause segregation of stone sizes. Take care not to dislodge the underlying base or filter when placing the stones.

The toe of the riprap slope should be keyed to a stable foundation at its base as shown in Figure 6.15b. The toe should be excavated to a depth about 1.5 times the design thickness of the riprap, and should extend horizontally from the slope.

The finished slope should be free of pockets of small stone or clusters of large stones. Hand placing may be necessary to achieve the proper distribution of stone sizes to produce a relatively smooth, uniform surface. The finished grade of the riprap should blend with the surrounding area. No overfall or protrusion of riprap should be apparent.

MAINTENANCE

In general, once a riprap installation has been properly designed and installed it requires very little maintenance. Riprap should be inspected periodically for scour or dislodged stones. Control of weed and brush growth may be needed in some locations.

GRASS-LINED CHANNELS (NCDENR 6.30)

CONSTRUCTION SPECIFICATIONS

1. Remove all trees, brush, stumps, and other objectionable material from the foundation area, and dispose of properly

2. Excavate the channel, and shape it to neat lines and dimensions shown on the plans plus a 0.2-foot overcut around the channel perimeter to allow for bulking during seedbed preparations and sod buildup.

3. Remove and properly dispose of all excess soil so that surface water may enter the channel freely.

4. The procedure used to establish grass in the channel will depend upon the severity of TROWN litions ROLESVILLE: and selection of species. Protect the channel with mulch or a temporary liner sufficient to withstand PSP_23_04 anticipated velocities during the establishment period.

MAINTENANCE

During the establishment period, check grass-lined channels after every rainfall. After grass is established, periodically check the channel; check it after every heavy rainfall event. Immediately make repairs. It is particularly important to check the channel outlet and all road crossings for bank stability and evidence of piping or scour holes. Remove all significant sediment accumulations to maintain the designed carrying capacity. Keep the grass in a healthy, vigorous condition at all times, since it is the primary erosion protection for the channel.

TOWN OF WAKE FOREST: PSP-XX-XX

These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued.

Public Works/Engineering

These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued.

Planning



GROUND STABILIZATION AND MATERIALS HANDLING PRACTICES FOR COMPLIANCE WITH THE NCG01 CONSTRUCTION GENERAL PERMIT

Implementing the details and specifications on this plan sheet will result in the construction activity being considered compliant with the Ground Stabilization and Materials Handling sections of the NCG01 Construction General Permit (Sections E and F, respectively). The permittee shall comply with the Erosion and Sediment Control plan approved by the delegated authority having jurisdiction. All details and specifications shown on this sheet may not apply depending on site conditions and the delegated authority having jurisdiction.

	SECTION E: GROUND STABILIZATION				
	Required Ground Stabilization Timeframes				
	Sit	te Area Description	Stabilize within this many calendar days after ceasing land disturbance	Timeframe variations	
	(a)	Perimeter dikes, swales, ditches, and perimeter slopes	7	None	
	(b)	High Quality Water (HQW) Zones	7	None	
	(c)	Slopes steeper than 3:1	7	If slopes are 10' or less in length and are not steeper than 2:1, 14 days are allowed	
	(d)	Slopes 3:1 to 4:1	14	 -7 days for slopes greater than 50' in length and with slopes steeper than 4:1 -7 days for perimeter dikes, swales, ditches, perimeter slopes and HQW Zones -10 days for Falls Lake Watershed 	
	(e)	Areas with slopes flatter than 4:1	14	 -7 days for perimeter dikes, swales, ditches, perimeter slopes and HQW Zones -10 days for Falls Lake Watershed unless there is zero slope 	
Note: After the permanent cessation of construction activities, any areas with temporary ground stabilization shall be converted to permanent ground stabilization as soon as practicable but in no case longer than 90 calendar days after the last land disturbing activity. Temporary ground stabilization shall be maintained in a manner to render the surface stable against accelerated erosion until permanent ground stabilization is achieved.					
	GROUND STABILIZATION SPECIFICATION Stabilize the ground sufficiently so that rain will not dislodge the soil. Use one of the techniques in the table below:				

Temporary Stabilization	Permanent Stabilization
· · ·	
 Temporary grass seed covered with straw or other mulches and tackifiers Hydroseeding Rolled erosion control products with or without temporary grass seed Appropriately applied straw or other mulch Plastic sheeting Image: Appropriate and tackifiers Image: Appropriate	 Permanent grass seed covered with straw or other mulches and tackifiers Geotextile fabrics such as permanent soil reinforcement matting Hydroseeding Shrubs or other permanent plantings covered with mulch Uniform and evenly distributed ground cover sufficient to restrain erosion Structural methods such as concrete, asphalt or retaining walls Rolled erosion control products with grass seed

POLYACRYLAMIDES (PAMS) AND FLOCCULANTS

- 1. Select flocculants that are appropriate for the soils being exposed during
- construction, selecting from the NC DWR List of Approved PAMS/Flocculants. 2. Apply flocculants at or before the inlets to Erosion and Sediment Control Measures.
- 3. Apply flocculants at the concentrations specified in the *NC DWR List of Approved*
- PAMS/Flocculants and in accordance with the manufacturer's instructions. 4. Provide ponding area for containment of treated Stormwater before discharging offsite.
- 5. Store flocculants in leak-proof containers that are kept under storm-resistant cover or surrounded by secondary containment structures.

NCG01 GROUND STABILIZATION AND MATERIALS HANDER HANDER OF CONSTRUCTION END

EQUIPMENT AND VEHICLE MAINTENANCE

- 1. Maintain vehicles and equipment to prevent discharge of fluids.
- 2. Provide drip pans under any stored equipment.
- 3. Identify leaks and repair as soon as feasible, or remove leaking equipment from the project.
- 4. Collect all spent fluids, store in separate containers and properly dispose as hazardous waste (recycle when possible).
- 5. Remove leaking vehicles and construction equipment from service until the problem has been corrected.
- 6. Bring used fuels, lubricants, coolants, hydraulic fluids and other petroleum products to a recycling or disposal center that handles these materials.

LITTER, BUILDING MATERIAL AND LAND CLEARING WASTE

- 1. Never bury or burn waste. Place litter and debris in approved waste containers. 2. Provide a sufficient number and size of waste containers (e.g dumpster, trash receptacle) on site to contain construction and domestic wastes.
- 3. Locate waste containers at least 50 feet away from storm drain inlets and surface waters unless no other alternatives are reasonably available.
- 4. Locate waste containers on areas that do not receive substantial amounts of runoff from upland areas and does not drain directly to a storm drain, stream or wetland. 5. Cover waste containers at the end of each workday and before storm events or
- provide secondary containment. Repair or replace damaged waste containers. 6. Anchor all lightweight items in waste containers during times of high winds.
- 7. Empty waste containers as needed to prevent overflow. Clean up immediately if containers overflow.
- 8. Dispose waste off-site at an approved disposal facility.
- 9. On business days, clean up and dispose of waste in designated waste containers.

PAINT AND OTHER LIQUID WASTE

- 1. Do not dump paint and other liquid waste into storm drains, streams or wetlands. 2. Locate paint washouts at least 50 feet away from storm drain inlets and surface waters unless no other alternatives are reasonably available.
- 3. Contain liquid wastes in a controlled area.
- 4. Containment must be labeled, sized and placed appropriately for the needs of site. 5. Prevent the discharge of soaps, solvents, detergents and other liquid wastes from
- construction sites.

PORTABLE TOILETS

- Install portable toilets on level ground, at least 50 feet away from storm drains, streams or wetlands unless there is no alternative reasonably available. If 50 foot offset is not attainable, provide relocation of portable toilet behind silt fence or place on a gravel pad and surround with sand bags.
- 2. Provide staking or anchoring of portable toilets during periods of high winds or in high foot traffic areas.
- Monitor portable toilets for leaking and properly dispose of any leaked material. Utilize a licensed sanitary waste hauler to remove leaking portable toilets and replace with properly operating unit.

EARTHEN STOCKPILE MANAGEMENT

- 1. Show stockpile locations on plans. Locate earthen-material stockpile areas at least 50 feet away from storm drain inlets, sediment basins, perimeter sediment controls and surface waters unless it can be shown no other alternatives are reasonably available.
- Protect stockpile with silt fence installed along toe of slope with a minimum offset of five feet from the toe of stockpile.
- Provide stable stone access point when feasible.
- Stabilize stockpile within the timeframes provided on this sheet and in accordance with the approved plan and any additional requirements. Soil stabilization is defined as vegetative, physical or chemical coverage techniques that will restrain accelerated erosion on disturbed soils for temporary or permanent control needs.



PART III SELF-INSPECTION, RECORDKEEPING AND REPORTING

SECTION A: SELF-INSPECTION

Self-inspections are required during normal business hours in accordance with the table below. When adverse weather or site conditions would cause the safety of the inspection personnel to be in jeopardy, the inspection may be delayed until the next business day on which it is safe to perform the inspection. In addition, when a storm event of equal to or greater than 1.0 inch occurs outside of normal business hours, the self-inspection shall be performed upon the commencement of the next business day. Any time when inspections were delayed shall be noted in the Inspection Record.

Inspect	Frequency (during normal business hours)	Inspection records must include:
(1) Rain gauge maintained in good working order	Daily	Daily rainfall amounts. If no daily rain gauge observations are made during weekend or holiday periods, and no individual-day rainfall information is available, record the cumulative rain measurement for those un- attended days (and this will determine if a site inspection is needed). Days on which no rainfall occurred shall be recorded as "zero." The permittee may use another rain-monitoring device approved by the Division.
(2) E&SC Measures	At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours	 Identification of the measures inspected, Date and time of the inspection, Name of the person performing the inspection, Indication of whether the measures were operating properly, Description of maintenance needs for the measure, Description, evidence, and date of corrective actions taken.
(3) Stormwater discharge outfalls (SDOs)	At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours	 Identification of the discharge outfalls inspected, Date and time of the inspection, Name of the person performing the inspection, Evidence of indicators of stormwater pollution such as oil sheen, floating or suspended solids or discoloration, Indication of visible sediment leaving the site, Description, evidence, and date of corrective actions taken.
(4) Perimeter of site	At least once per 7 calendar days and within 24 hours of a rain event ≥ 1.0 inch in 24 hours	 If visible sedimentation is found outside site limits, then a record of the following shall be made: 1. Actions taken to clean up or stabilize the sediment that has left the site limits, 2. Description, evidence, and date of corrective actions taken, and 3. An explanation as to the actions taken to control future releases.
(5) Streams or wetlands onsite or offsite (where accessible)	At least once per 7 calendar days and within 24 hours of a rain event \geq 1.0 inch in 24 hours	 If the stream or wetland has increased visible sedimentation or a stream has visible increased turbidity from the construction activity, then a record of the following shall be made: 1. Description, evidence and date of corrective actions taken, and 2. Records of the required reports to the appropriate Division Regional Office per Part III, Section C, Item (2)(a) of this permit.
(6) Ground stabilization measures	After each phase of grading	 The phase of grading (installation of perimeter E&SC measures, clearing and grubbing, installation of storm drainage facilities, completion of all land-disturbing activity, construction or redevelopment, permanent ground cover). Documentation that the required ground stabilization measures have been provided within the required timeframe or an assurance that they will be provided as soon as possible.

PART II, SECTION G, ITEM (4) DRAW DOWN OF SEDIMENT BASINS FOR MAINTENANCE OR CLOSE OUT

Sediment basins and traps that receive runoff from drainage areas of one acre or more shall use outlet structures that withdraw water from the surface when these devices need to be drawn down for maintenance or close out unless this is infeasible. The circumstances in which it is not feasible to withdraw water from the surface shall be rare (for example, times with extended cold weather) Non-surface withdrawals from sediment basins shall be allowed only when all of the following criteria have been met:

NCG01 SELF-INSPECTION, RECORDKEEPING AND REPORTING

SELF-INSPECTION, REC	PART III CORDKEEPING AND REPORTING		
SECTION I 1. E&SC P The approved E&SC plan as well as any approved E&SC plan must be kept up-to- following items pertaining to the E&SC p at all times dur	S (a	Per a) V	
Item to Document	Documentation Requirements		
(a) Each E&SC measure has been installed and does not significantly deviate from the locations, dimensions and relative elevations shown on the approved E&SC plan.	Initial and date each E&SC measure on a copy of the approved E&SC plan or complete, date and sign an inspection report that lists each E&SC measure shown on the approved E&SC plan. This documentation is required upon the initial installation of the E&SC measures or if the E&SC measures are modified after initial installation.	 They T Th (c) Releases of had of the Clean V 	are le They d ey ar azardo Nater
(b) A phase of grading has been completed.	Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate completion of the construction phase.	((e) Noncomplia	d) A
(c) Ground cover is located and installed in accordance with the approved E&SC plan.	Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate compliance with approved ground cover specifications.	After a permittee the appropriate D	2. Re becor Divisio
 (d) The maintenance and repair requirements for all E&SC measures have been performed. 	Complete, date and sign an inspection report.	other requiremen reported to th	its list ie Dep
(e) Corrective actions have been taken to E&SC measures.	Initial and date a copy of the approved E&SC plan or complete, date and sign an inspection report to indicate the completion of the corrective action.	Occurrence	Ron
2. Additional Documentation to be Kept on In addition to the E&SC plan documents a site and available for inspectors at all time	Site bove, the following items shall be kept on the es during normal business hours, unless the	(a) Visible sediment deposition in a stream or wetland	• V • V • V s

Division or a similar inspection form that includes all the required elements. Use of electronically-available records in lieu of the required paper copies will be allowed if

this requirement not practical:

shown to provide equal access and utility as the hard-copy records. **3. Documentation to be Retained for Three Years** All data used to complete the e-NOI and all inspection records shall be maintained for a period of three years after project completion and made available upon request. [40 CFR 122.41]

Division provides a site-specific exemption based on unique site conditions that make

(b) Records of inspections made during the previous twelve months. The permittee shall

record the required observations on the Inspection Record Form provided by the

(a) This General Permit as well as the Certificate of Coverage, after it is received.

(a) The E&SC plan authority has been provided with documentation of the non-surface withdrawal and the specific time periods or conditions in which it will occur. The non-surface withdrawal shall not commence until the E&SC plan authority has approved these items,

(b) The non-surface withdrawal has been reported as an anticipated bypass in accordance with Part III, Section C, Item (2)(c) and (d) of this permit,

(c) Dewatering discharges are treated with controls to minimize discharges of pollutants from stormwater that is removed from the sediment basin. Examples of appropriate controls include properly sited, designed and maintained dewatering tanks, weir tanks, and filtration systems,

(d) Vegetated, upland areas of the sites or a properly designed stone pad is used to the extent feasible at the outlet of the dewatering treatment devices described in Item (c) above,

(e) Velocity dissipation devices such as check dams, sediment traps, and riprap are provided at the discharge points of all dewatering devices, and

(f) Sediment removed from the dewatering treatment devices described in Item (c) above is disposed of in a manner that does not cause deposition of sediment into waters of the United States

This approval is valid upo plans. Any work authorize accordance with the plans electronic approval may no modification of this approv approval.

(b) Oil spills and

1(b)-(c) above

122.41(m)(3)]

(c) Anticipated

bypasses [40 CFR

(d) Unanticipated bypasses [40 CFR 122.41(m)(3)]

(e) Noncompliance with the conditions

of this permit that

may endanger

environment[40 CFR 122.41(I)(7)]

health or the

substances per Item

release of

hazardous

City of Raleigh Developmen

Raleigh Water Review Offic

PART III LF-INSPECTION, RECORDKEEPING <u>SECTION C: REPORT</u> 1. Occurrences that Must b Permittees shall report the follo Visible sediment deposition in (b) Oil spills if	G AND REPORTING ING e Reported wing occurrences: a stream or wetland.		EXULT® ENGINEERING BNGLicense 301 S. Main Street Kannapolis, NC 28081 980.495.2250 www.exultengineering.com
 They are 25 gallor re less than 25 gallons but cannolley cause sheen on surface water y are within 100 feet of surface water y are within 100 feet of surface water at (Ref: 40 CFR 110.3 and 4 (Ref: 40 CFR 302.4) or G Anticipated bypasses and una ce with the conditions of this per environmer Reporting Timeframes and Oth ecomes aware of an occurrence of vision regional office within the t s listed below. Occurrences outsi Department's Environmental Em 858-0368. 	t be cleaned up within 24 hours, rs (regardless of volume), or vaters (regardless of volume). eportable quantities under Section 311 0 CFR 117.3) or Section 102 of CERCLA .S. 143-215.85. Inticipated bypasses. mit that may endanger health or the nt. Ther Requirements that must be reported, he shall contact imeframes and in accordance with the ide normal business hours may also be hergency Center personnel at (800)		PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
 Reporting Timeframes (After Discov. Within 24 hours, an oral or electr. Within 7 calendar days, a report sediment and actions taken to ad Division staff may waive the requirease-by-case basis. If the stream is named on the NC related causes, the permittee ma monitoring, inspections or apply determine that additional required with the federal or state impaired. Within 24 hours, an oral or electrishall include information about the location of the spill or release. A report at least ten days before. The report shall include an evaluate effect of the bypass. Within 24 hours, an oral or electric within 7 calendar days, a report quality and effect of the bypass. Within 24 hours, an oral or electric transmitter of the spill or release. Within 7 calendar days, a report quality and effect of the bypass. Within 7 calendar days, a report noncompliance, and its causes; the including exact dates and times, a been corrected, the anticipated t continue; and steps taken or plar prevent reoccurrence of the none. Division staff may waive the required as a sport of the spill or plar prevent reoccurrence of the none. 	very) and Other Requirements ronic notification. that contains a description of the dress the cause of the deposition. irement for a written report on a 303(d) list as impaired for sediment- y be required to perform additional more stringent practices if staff ements are needed to assure compliance d-waters conditions. ronic notification. The notification he date of the bypass, if possible. ation of the anticipated quality and ronic notification. that includes an evaluation of the nonic notification. that contains a description of the noncompliance is expected to and if the noncompliance has not ime noncompliance is expected to and to reduce, eliminate, and compliance. [40 CFR 122.41(l)(6). irement for a written report on a		SEAL OPTICE OR CONSTRUCTION SEAL OPTICE OR CONSTRUCTION SEAL OPTICE OR CONSTRUCTION SEAL OPTICE OR CONSTRUCTION SEAL OPTICE OR CONSTRUCTION SEAL OPTICE OR CONSTRUCTION
ANS AUTHORIZED FOR CONSTRUCTION This approval is being issued electronically. Upon the signature of a City of Raleigh The City will retain a copy of the approved orized by this approval must proceed in plans kept on file with the City. This hay not be edited once issued. Any opproval once issued will invalidate this	TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX These class have been electronically approved for construction by the town of Wake Forest Public Works and Engineering Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approva- may not be altered once issued.	JOB NO.: 00103002 DESIGNED BY: DATE: 10/23/24 REVIEWED BY: E. LYNC	SCALE: 1" = 50' REVISIONS
v Officer	Planning		EC-18





Page:





NG AND PAVEMENT MARKING NOTES	LEGEND	FINAL PAVEMENT M
E AND DISPOSE OF EXISTING "U" CHANNEL POST. EXISTING SIGN ON NEW "U" CHANNEL POST. E AND DISPOSE OF EXISTING SIGNS AND "U" INEL POST. ACKGROUND FOR TYPE E & F SHALL BE TYPE C ECTIVE SHEETING. TREET NAME SIGNS SHALL ADHERE TO 2023 MUTCD. STREET NAME SIGNS SHALL BE APPROVED BY THE IPORTATION AND FACILITIES DEPARTMENT STAFF OR TO INSTALLATION. ACTOR TO TIE PROPOSED MARKINGS TO STING MARKINGS AT PROJECT LIMITS. ACTOR SHALL MILL ANY EXISTING (INGS OR SYMBOLS IN CONFLICT WITH THE POSED MARKINGS. D REFLECTIVE PAVEMENT MARKERS ARE TO BE DED ACCORDING TO NCDOT ROADWAY STANDARD WINGS.	 CRYSTAL/RED PAVEMENT MARKERS YELLOW/YELLOW PAVEMENT MARKERS EXISTING TRAFFIC SIGNAL PROPOSED TRAFFIC SIGNAL PROPOSED SIGN LOCATION ON "U" CHANNEL POST EXISTING SIGN LOCATION ON "U" CHANNEL POST 	PAVEMENT MARKING LINES T1 - THERMOPLASTIC (4" WHITE, 90 MILS T2 - THERMOPLASTIC (4" WHITE, 90 MILS T4 - THERMOPLASTIC (4" WHITE, 90 MILS T5 - THERMOPLASTIC (4" WHITE, 90 MILS T10 - THERMOPLASTIC (4" YELLOW, 90 MIL T11 - THERMOPLASTIC (4" YELLOW, 90 MIL T12 - THERMOPLASTIC (4" YELLOW, 90 MIL T13 - THERMOPLASTIC (4" YELLOW, 90 MIL T14 - THERMOPLASTIC (4" YELLOW, 90 MIL T42 - THERMOPLASTIC (4" YELLOW, 90 MIL T51 - THERMOPLASTIC (4" YELLOW, 90 MIL T52 - THERMOPLASTIC (24" WHITE, 90 MIL T52 - THERMOPLASTIC (24" WHITE, 90 MIL T62 - THERMOPLASTIC (24" WHITE, 90 MIL T63 - THERMOPLASTIC (24" WHITE, 90 MIL T64 - THERMOPLASTIC (WHITE, 90 MILS) T75 - THERMOPLASTIC (WHITE, 90 MILS) T74 - THERMOPLASTIC (WHITE, 90 MILS)



LEGEND	FINAL PAVEMENT
CRYSTAL/RED PAVEMENT MARKERS	PAVEMENT MARKING LINES
YELLOW/YELLOW PAVEMENT MARKERS	T4 - THERMOPLASTIC (4" WHITE, 90 MIL T5 - THERMOPLASTIC (4" WHITE, 90 MIL T5 - THERMOPLASTIC (4" WHITE, 90 MIL
EXISTING TRAFFIC SIGNAL	T10 - THERMOPLASTIC (4" YELLOW, 90 MI T11 - THERMOPLASTIC (4" YELLOW, 90 MI T12 - THERMOPLASTIC (4" YELLOW, 90 MI T13 - THERMOPLASTIC (4" YELLOW, 90 MI T14 - THERMOPLASTIC (4" YELLOW, 90 MI T42 - THERMOPLASTIC (8" YELLOW, 90 MI
<pre>PROPOSED TRAFFIC SIGNAL</pre>	T51 - THERMOPLASTIC (12" WHITE, 90 MI T52 - THERMOPLASTIC (12" YELLOW, 90 M T61 - THERMOPLASTIC (24" WHITE, 90 MI T62 - THERMOPLASTIC (24" WHITE, 90 MI
PROPOSED SIGN LOCATION ON "U" CHANNEL POST EXISTING SIGN LOCATION ON "U" CHANNEL POST	PAVEMENT MARKING SYMBO T70 - THERMOPLASTIC (WHITE, 90 MILS) T71 - THERMOPLASTIC (WHITE, 90 MILS) T72 - THERMOPLASTIC (WHITE, 90 MILS) T74 - THERMOPLASTIC (WHITE, 90 MILS)
	LEGEND Image: CRYSTAL/RED PAVEMENT MARKERS ◆ YELLOW/YELLOW PAVEMENT MARKERS Image: EXISTING TRAFFIC SIGNAL Image: PROPOSED TRAFFIC SIGNAL Image: PROPOSED SIGN LOCATION ON "U" CHANNEL POST Image: EXISTING SIGN LOCATION ON "U" CHANNEL POST

		Image: Constraint of the constraint
SEE NOTES 1 & 2 -L4- STA 20+37		PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
$\frac{11'}{12}$	MATCHLINE -L4- STA 21+50 (SEE SHEET PM-3)	PAVEMENT MARKING AND SIGNING PLAN
	TOWN OF ROLESVILLE: PSP-23-04 TOWN OF WAKE FOREST: PSP-XX-XX These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued.	SEAL PRELIMENT ARY PLIANS DO NOT USE FOR CONSTRUCTION SIGNATURE DATE SIGNATURE DATE
MARKINGS S) EDGELINE S) SOLID LANE LINE S) SOLID LANE LINE S) SOLID LANE LINE S) 2' x 6'/SP MINI-SKIP S) EDGELINE S) SINGLE CENTER LINE S) 10' SKIP S) DOUBLE CENTER LINE S) 2' x 6'/SP MINI-SKIP S) DIAGONAL S) DIAGONAL S) DIAGONAL S) DIAGONAL S) STOP BAR S) CROSSWALK LS LEFT TURN ARROW RIGHT TURN ARROW RIGHT ARROW RIGHT/STRAIGHT ARROW	Planning CITY OF RALEIGH – PLANS AUTHORIZED FOR CONSTRUCTION Electronic Approval: This approval is being issued electronically. This approval is valid upon the signature of a City of Raleigh Review Officer below. The City will retain a copy of the approved plans. Any work authorized by this approval must proceed in accordance with the plans kept on file with the City. This electronic approval may not be edited once issued. Any modification of this approval once issued will invalidate this approval. City of Raleigh Development Approval: Raleigh Water Review Officer	JOB NO.: 00103002 DESIGNED L DATE: 10/23/24 REVIEWED L SCALE: 1"=50' REVISIONS BHEET NO. BWD-7



ING AND PAVEMENT MARKING NOTES	LEGEND	FINAL PAVEMENT
VE AND DISPOSE OF EXISTING "U" CHANNEL POST.	CRYSTAL/RED PAVEMENT MARKERS	PAVEMENT MARKING LINES
T EXISTING SIGN ON NEW "U" CHANNEL POST. VE AND DISPOSE OF EXISTING SIGNS AND "U" NNEL POST.	YELLOW/YELLOW PAVEMENT MARKERS	T4 - THERMOPLASTIC (4" WHITE, 90 MILS T4 - THERMOPLASTIC (4" WHITE, 90 MILS T5 - THERMOPLASTIC (4" WHITE, 90 MILS T10 - THERMOPLASTIC (4" WHITE, 90 MILS
BACKGROUND FOR TYPE E & F SHALL BE TYPE C LECTIVE SHEETING. STREET NAME SIGNS SHALL ADHERE TO 2023 MUTCD. . STREET NAME SIGNS SHALL BE APPROVED BY THE NPORTATION AND FACILITIES DEPARTMENT STAFF	EXISTING TRAFFIC SIGNAL	T10 - THERMOPLASTIC (4 YELLOW, 90 MIL T11 - THERMOPLASTIC (4" YELLOW, 90 MIL T12 - THERMOPLASTIC (4" YELLOW, 90 MIL T13 - THERMOPLASTIC (4" YELLOW, 90 MIL T14 - THERMOPLASTIC (4" YELLOW, 90 MIL T42 - THERMOPLASTIC (8" YELLOW, 90 MIL
OR TO INSTALLATION. RACTOR TO TIE PROPOSED MARKINGS TO STING MARKINGS AT PROJECT LIMITS. RACTOR SHALL MILL ANY EXISTING RKINGS OR SYMBOLS IN CONFLICT WITH THE	<pre> PROPOSED TRAFFIC SIGNAL </pre>	T51 - THERMOPLASTIC (12" WHITE, 90 MIL T52 - THERMOPLASTIC (12" YELLOW, 90 MJ T61 - THERMOPLASTIC (24" WHITE, 90 MIL T62 - THERMOPLASTIC (24" WHITE, 90 MIL
PPOSED MARKINGS. ED REFLECTIVE PAVEMENT MARKERS ARE TO BE CED ACCORDING TO NCDOT ROADWAY STANDARD WINGS.	PROPOSED SIGN LOCATION ON "U" CHANNEL POST EXISTING SIGN LOCATION ON "U" CHANNEL POST	PAVEMENT MARKING SYMBO T70 - THERMOPLASTIC (WHITE, 90 MILS) T71 - THERMOPLASTIC (WHITE, 90 MILS) T72 - THERMOPLASTIC (WHITE, 90 MILS) T74 - THERMOPLASTIC (WHITE, 90 MILS)

		NCLicense BOL L T Solution MCLicense 301.S. Main Street MCLicense 301.S. Main Street MCLicense 301.S. Main Street MCLicense 980.495.2250 www.exultengineering.com
		PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
-L4- STA 33+25		PAVEMENT MARKING AND SIGNING PLAN
MARKINGS S) EDGELINE S) SOLID LANE LINE S) SOLID LANE LINE S) 3' x 9'/SP MINI-SKIP S) 2' x 6'/SP MINI-SKIP LS) EDGELINE LS) SINGLE CENTER LINE LS) DUBLE CENTER LINE LS) DUBLE CENTER LINE LS) 2' x 6'/SP MINI-SKIP LS) DIAGONAL LS) DIAGONAL LS) DIAGONAL LS) DIAGONAL LS) STOP BAR LS) CROSSWALK	Standard	Image: Notice of the service of the
LEFT TURN ARROW RIGHT TURN ARROW STRAIGHT ARROW RIGHT/STRAIGHT ARROW	Raleigh Water Review Officer	PM-3



1264.02 OBJECT MARKERS - INSTALLATION

ING AND PAVEMENT MARKING NOTES	LEGEND	FINAL PAVEMENT MAR
VE AND DISPOSE OF EXISTING "U" CHANNEL POST.	CRYSTAL/RED PAVEMENT MARKERS	PAVEMENT MARKING LINES
VE AND DISPOSE OF EXISTING SIGNS AND "U"	YELLOW/YELLOW PAVEMENT MARKERS	T2 - THERMOPLASTIC (4 WHITE, 90 MILS) T4 - THERMOPLASTIC (4" WHITE, 90 MILS) T5 - THERMOPLASTIC (4" WHITE, 90 MILS)
BACKGROUND FOR TYPE E & F SHALL BE TYPE C LECTIVE SHEETING. STREET NAME SIGNS SHALL ADHERE TO 2023 MUTCD. STREET NAME SIGNS SHALL BE APPROVED BY THE ANPORTATION AND FACILITIES DEPARTMENT STAFF	EXISTING TRAFFIC SIGNAL	T10 - THERMOPLASTIC (4 YELLOW, 90 MILS) T11 - THERMOPLASTIC (4" YELLOW, 90 MILS) T12 - THERMOPLASTIC (4" YELLOW, 90 MILS) T13 - THERMOPLASTIC (4" YELLOW, 90 MILS) T14 - THERMOPLASTIC (4" YELLOW, 90 MILS) T42 - THERMOPLASTIC (8" YELLOW, 90 MILS)
TO INSTALLATION. RACTOR TO TIE PROPOSED MARKINGS TO ISTING MARKINGS AT PROJECT LIMITS. RACTOR SHALL MILL ANY EXISTING RKINGS OR SYMBOLS IN CONFLICT WITH THE	<pre> PROPOSED TRAFFIC SIGNAL </pre>	T51 - THERMOPLASTIC (12" WHITE, 90 MILS) T52 - THERMOPLASTIC (12" YELLOW, 90 MILS) T61 - THERMOPLASTIC (24" WHITE, 90 MILS) T62 - THERMOPLASTIC (24" WHITE, 90 MILS)
DPOSED MARKINGS. ED REFLECTIVE PAVEMENT MARKERS ARE TO BE ACED ACCORDING TO NCDOT ROADWAY STANDARD WINGS.	PROPOSED SIGN LOCATION ON "U" CHANNEL POST EXISTING SIGN LOCATION ON "U" CHANNEL POST	PAVEMENT MARKING SYMBOLS T70 - THERMOPLASTIC (WHITE, 90 MILS) L T71 - THERMOPLASTIC (WHITE, 90 MILS) R T72 - THERMOPLASTIC (WHITE, 90 MILS) S T74 - THERMOPLASTIC (WHITE, 90 MILS) R

		Image: Construction Image: Construction Image: Construction Image: Construction NC License 301 S. Main Street Street Street MC License 980.495.2250 www.exultengineering.com
		PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
		PAVEMENT MARKING AND SIGNING PLAN
MARKINGS S ILS) EDGELINE ILS) SOLID LANE LINE ILS) SOLID LANE LINE ILS) 3' x 9'/SP MINI-SKIP ILS) 2' x 6'/SP MINI-SKIP ILS) 2' x 6'/SP MINI-SKIP MILS) EDGELINE MILS) SINGLE CENTER LINE	TOWN OF ROLESVILLE: DSP-23-04 TOWN OF WAKE FOREST: DSP-XX-XX These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Public Works and Engineering Departments. This approval may not be altered once issued. Public Works/Engineering These plans have been electronically approved for construction by the Town of Wake Forest Planning Department. This approval may not be altered once issued. Planning CITY OF RALEIGH – PLANS AUTHORIZED FOR CONSTRUCTION Electronic Approval: This approval is being issued electronically.	SEAL CAROL NORTH CAROL NOFESSION SEAL PRELIMINARY PLIANS DO NOT USE FOR CONSTRUCTION NGINEER NGINEER NGINEER SIGNATURE DATE DATE DATE DATE DATE DATE
MILS) 10' SKIP MILS) DOUBLE CENTER LINE MILS) 2' x 6'/SP MINI-SKIP MILS) DIAGONAL MILS) DIAGONAL MILS) DIAGONAL MILS) STOP BAR MILS) CROSSWALK BOLS) LEFT TURN ARROW) RIGHT TURN ARROW) STRAIGHT ARROW) STRAIGHT ARROW	This approval is valid upon the signature of a City of Raleigh Review Officer below. The City will retain a copy of the approved plans. Any work authorized by this approval must proceed in accordance with the plans kept on file with the City. This electronic approval may not be edited once issued. Any modification of this approval once issued will invalidate this approval. City of Raleigh Development Approval: Raleigh Water Review Officer	<u>JOB NO.: 001030</u> <u>DATE: 102324</u> SCALE: 1"=50' REVISIONS REEVISIONS





ING AND PAVEMENT MARKING NOTES	LEGEND	FINAL PAVEMENT N
VE AND DISPOSE OF EXISTING "U" CHANNEL POST.	CRYSTAL/RED PAVEMENT MARKERS	PAVEMENT MARKING LINES
VE AND DISPOSE OF EXISTING SIGNS AND "U" ANNEL POST.	YELLOW/YELLOW PAVEMENT MARKERS	T4 - THERMOPLASTIC (4 WHITE, 90 MILS T4 - THERMOPLASTIC (4" WHITE, 90 MILS T5 - THERMOPLASTIC (4" WHITE, 90 MILS T10 - THERMOPLASTIC (4" YELLOW 90 MIL
BACKGROUND FOR TYPE E & F SHALL BE TYPE C FLECTIVE SHEETING. STREET NAME SIGNS SHALL ADHERE TO 2023 MUTCD. _ STREET NAME SIGNS SHALL BE APPROVED BY THE ANPORTATION AND FACILITIES DEPARTMENT STAFF	EXISTING TRAFFIC SIGNAL	T11 - THERMOPLASTIC (4" YELLOW, 90 MIL T12 - THERMOPLASTIC (4" YELLOW, 90 MIL T13 - THERMOPLASTIC (4" YELLOW, 90 MIL T13 - THERMOPLASTIC (4" YELLOW, 90 MIL T14 - THERMOPLASTIC (4" YELLOW, 90 MIL T42 - THERMOPLASTIC (8" YELLOW, 90 MIL
IOR TO INSTALLATION. RACTOR TO TIE PROPOSED MARKINGS TO ISTING MARKINGS AT PROJECT LIMITS. RACTOR SHALL MILL ANY EXISTING RKINGS OR SYMBOLS IN CONFLICT WITH THE	<pre> PROPOSED TRAFFIC SIGNAL </pre>	T51 - THERMOPLASTIC (12" WHITE, 90 MIL T52 - THERMOPLASTIC (12" YELLOW, 90 MI T61 - THERMOPLASTIC (24" WHITE, 90 MIL T62 - THERMOPLASTIC (24" WHITE, 90 MIL
DPOSED MARKINGS. ED REFLECTIVE PAVEMENT MARKERS ARE TO BE ACED ACCORDING TO NCDOT ROADWAY STANDARD AWINGS.	PROPOSED SIGN LOCATION ON "U" CHANNEL POST EXISTING SIGN LOCATION ON "U" CHANNEL POST	PAVEMENT MARKING SYMBO T70 - THERMOPLASTIC (WHITE, 90 MILS) T71 - THERMOPLASTIC (WHITE, 90 MILS) T72 - THERMOPLASTIC (WHITE, 90 MILS) T74 - THERMOPLASTIC (WHITE, 90 MILS)



	Image: Constraint of the constraint
	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
	PAVEMENT MARKING AND SIGNING PLAN
Set INE Set I	SEAL OR TH CARO OR TH CARO OR TH CARO SEAL PRELIMINAARY PLANS DO NOT USE YOR CONSTRUCTION MCINEER NOT USE YOR CONSTRUCTION DATE

270	130	120	110	100	90	80	70	60
260								
250								
240								
260								
050								
250								
240								
260								
250								
250								
240								
260								
250								
240								
260								
250								
							•F0	
240								
260								
250								
240								



							E R I N G n Street NC 28081 .2250 neering.com
80	90	100	110	120	130	270	3 I N E J 3801 S. Maii 980.495, . exultengi
	NOTE:	S: STING UNDERG	ROUND UTIL	ITIES ARE SI	HOWN HORIZON	VTALLY PER	
	TO BE	INFORMATION 3' BELOW EXI	I. VERTICA STING GROUN	L LOCATION . D.	IS UNKNOWN A	and Assumed 260	C License C 1445
						250	₹
						240	RO RO
							× [×] [×] [×]
						260	A A A
							UR PR PR
						250	Z Z Z
							L L A
						240	SVII AD
							RO.
						260	RO No
						250	
						240	
						260	S
						250	
							SEC
						240	SS
							L O A
						260	U U
						250	
						240	
						260	DATE
							G. BOY
						250	
							DESIGN
						240	
							0010300: 0/23/24 S
80	90	100	110	120	130		

	130	120	110	100	90	80	70	60
270								
110								
260							• ••• ••• ••• •••	
250								
240								
260								
250								
240								
260								
250								
240								
260								
					\			
250								
240								
260								
250								
240								
260							EX.EOP	
250								
240								



EOP



i 0.020

•FO •FO •FO









80	90 NOTE: 1. EXIS SURVEY TO BE (100 S: STING UNDERGI INFORMATION 3' BELOW EXIS	110 ROUND UTILI VERTICAL TING GROUN	120 ITIES ARE SHO LOCATION IS	130 DWN HORIZON S UNKNOWN AN	TALLY PER ND ASSUMED 270	Image: Non-Structure Image: Structure Image: Structure NC License 301 S. Main Street Street MC License Mon.exultengineering.com
						260	
						250	ROLIN
						240	A RM O VEV CA
						260	CE F IMPR VORT
							PEAF WAY ILLE, 1
						250	ROAD
						240	۳ ۵
						260	
						250	
						240	S
						260	A TION
						250	DADW S SEC
							CROS
						240	
						260	
						250	
						240	BOYLE LYNCH DATE
						260	SNED BY: G. WED BY: E.
						250	02 DESI- 4 REVIE
						240	F: 10/23/2. LE: 10/23/2. LE: EVISIONS
80	90	100	110	120	130		

130 120 110 100 90 80 70 60 5 280									
280 270 860 250 260 270 270 250 2		130	120	110	100	90	80	70	60 5
280 270 260 250 270 260 270 260 250 260 270 260 270 260 270 260 270 260 250 270 260 250 260 270 260 250 270 2									
280 270 260 250 280 270 260 270 260 270 260 250 260 250 270 260 270 260 250 270 260 250 270 260 250 2									
270 260 250 280 280 270 280 270 280 270 280 250 2	280								
280 250 280 280 280 270 250 270 280 250 270 280 250 270 250 270 250 270 250 270 250 270 250 270 250 250 250 250 250 250 250 250 250 250 250	270								
260 250 280 270 260 250 270 2									
250 280 270 260 250	260								
280 270 260 250 270 260 270 250 270 250 270 250 270 250 270 250 250 250 250 250 250 250 250 250 250	250								
280 270 260 250 270 260 250									
270	280								
260 250 270 260 250 250 260 250 270 260 270 260 250 260 250 250 250 250 250 250 250 250 250 250	270								
250 270 260 250 270 260 270 260 270 260 250 260 250 250 250 250 250 250 250 250 250 250 250	260								
250 270 260 250 270 260 250 270 260 250 250 250 250 250 250 250 250 250 250 250 250 250	200								
270	250								
260 250 270 260 250 250 250 250 250 250 250 250 250 250 250 250 250	270								
260 250 270 260 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250									
250 270 260 250 270 260 250	260								
270 260 250 270 260 250	250								
260 250 270 260 250	070								
260 250 270 260 260 250	270								
250 270 260 250	260								
270 260 250	250								
270									
260	270								
250	260								
	250								

130 120 110 100 90 80 70 60 5		130	120	110	100	90	80	70	60 5









	90 100 NOTES: 1. EXISTING UNDERG SURVEY INFORMATION TO BE 3' BELOW EXIS	110 ROUND UTILIT VERTICAL STING GROUND.	120 IES ARE SHOW LOCATION IS	130 N HORIZONT/ UNKNOWN ANI	ALLY PER D ASSUMED		NC License 301 S. Main Street X0 L T Image: Street NC License 301 S. Main Street 980.495.2250 #C-4445 www.exultengineering.com
					280 270		M EMENTS CAROLINA
BY MCADAMS					260		CE FAR/ IMPROV VORTH
					280		PEAR ADWAY SVILLE, N
					270		ROLE
					260 250		
					270		S
					260		ADWAY SECTIO
					250 270		CROSS
					260		
					250		
					270 260	VED BY: G. BOYLE VED BY: E. LYNCH	INIT. DAT
					250	JOB NO.: 00103002 DESIGN DATE: 10/23/24 REVIEW	SCALE: REVISIONS
80	90 100	110	120	130		\square	sheet no. X-3

	130	120	110	100	90	80	70	60	
290									
290									
270									
260									
250									
280									
270									
260									
250									
220									
280									
270									
260									
250									
280									
									- TCE
270								• • • • • • • • • • • • • • • • • • •	
260									
250									



18+06.00







80	90 NOTES 1. EXIS SURVEY TO BE 3	100 S: STING UNDERC INFORMATION B' BELOW EXI	110 ROUND UTILI N. VERTICAL STING GROUN	120 TIES ARE SH LOCATION I	130 IOWN HORIZON S UNKNOWN A	TALLY PER ND ASSUMED	E E L T ® Image: Second stress of the second
						290 280 270 260 250	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						280 270	
						260 250	DWAY SECTIONS
						280 270	CROSS S
						260 250	
						280	DESIGNED BY: G. BOYLE REVIEWED BY: E. LYNCH INIT. DATE
BY MCADAMS						260 250	JOB NO.: 00103002 DATE: 10/23/24 SCALE: REVISIONS ON LEAN
80	90	100	110	120	130		X-4

	130 120 11	0 100 90 80	70 60 50	30 20 10 0	10 20 30	40 50 60	70 80	90
								NOTES: 1. EXISTIN
								SURVEY INF TO BE 3' B
290								
					NON CONTRACTOR OF			
280								
					575.10 275.10 275.00 0.000			
					•FO			
270								
260				20 + 00 .				
280				. TCE ROW K.EOP 07	EoP 57 - EX.F			
					0.020 0.020 7 0.020 0.120 0.160 0.25	<u>s</u>		
270					•FO	.		
				GAS, CAS, CAS, CAS, CAS, CAS, CAS, CAS, C				
				19+90.0	00			
260								
290								
					EX, ROW			
280				Second Seco	EOP 4			
					0.020 0.020 Z			
270					• • • • • • • • • • • • • • • • • • •			
				ZICIAL CARPACING CARPANEL				
260				19+50	00			
290								
280				P.70				
				EL 17 EL 17 EZ				
270					• • • • • • • • • • • • • • • • • • •			
260				·····································	$\frown \frown \frown \frown = = = = = = = = = = = = = = = =$			
250				-//- Forpetu	ille Road			
	130 120 11	0 100 90 80	70 60 50	30 20 10 0	10 20 30	40 50 60	70 80 9	90







90 100 110 120 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SURVEY INFORMATION. VERTICAL LOCATIO TO BE 3' BELOW EXISTING GROUND.	NC License #C-4445 Www.exultengineering.com
	260 ROADWAY IMPROVEMENTS ROLINA ROLESVILLE, NORTH CAROLINA 260 260 260 260
	280 270 260 290 280 270 270 260 270
	260 270 260 130 130 130 250 130 250 130 250 130 250 250 130 250 130 250 250 130 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 130 250 250 250 250 250 250 250 250 250 25

300	130	120		100	90	80	70	60	
290									
280									
270									
290									
280									
210									
230									
270									
290									
280									
270									
260									
280						N			
270									
260									
280									
270									
260									
	130	120	110	100	90	80	70	60	















80	90 100	110 120	130	U L T ® E E R I N G Main Street bls, NC 28081 495.2250 engineering.com
	NOTES: 1. EXISTING UNDERGRO SURVEY INFORMATION. TO BE 3' BELOW EXIST:	UND UTILITIES ARE SHOWN VERTICAL LOCATION IS UN ING GROUND.	HORIZONTALLY PER IKNOWN AND ASSUMED 290	NC License #C-4445 Kannapo B0. www.exult
			280	SNA
			270	
			290	FARN PROVE RTH O
			280	
			270	PE
			290	ROLE
			280	
			270	
			290	S
			280	AY CTION
			270	DADW S SEC
			260	CROS
			220	
			270	
			260	Y: G. BOYLE
			280	REVIEWED B
			270	00103002 1023/24 NS
			260	DATE: DATE: SCALE: REVISION SHEET NO.
80	90 100	110 120	130	X–6

	130	120	110	100	90	80	70	60	
310									
300									
						/ /			-
290									
280									
300									
290									
280									
300									
							• • • • • •		
290									
280									
300									
290									-
280									
270									
290									
									-
290									
070									
210									



80	90	100	110	120	130		X U L T ® G I N E E R I N G 301 S. Main Street annapolis, NC 28081 980.495.2250 v.exultengineering.com
	NOTES 1. EXIS SURVEY TO BE S	S: STING UNDERGF INFORMATION 3' BELOW EXIS	ROUND UTIL: VERTICAL TING GROUN	ITIES ARE SH LOCATION : D.	HOWN HORIZON IS UNKNOWN A	ITALLY PER ND ASSUMED	NC License #C-4445 www
						310 300 290 280	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						290	SNO
						290	ROADWAY CROSS SECTIO
						290 280 270	. BOYLE LYNCH . DATE
						290 280 270	JOB NO.: 00103002 DESIGNED BY: G. DATE: 1023/24 REVIEWED BY: E. SCALE: REVISIONS INIT
80	90	100	110	120	130		SHEET NO. X-7

	100	100	110	100			7 0	
					90	80		6U
360								
350								
340								
360								
350								
340								
360								
350								
340								
360								
350								
340								
700								
360								
350								
7.40								
540								
360								
750								
550								
340								
JJU								





i •fo



346.17 • **8**0 s • **9**0 s

• FO

20+00.00



							L R R I N G Street C 28081 2250 eering.com
80	90	100	110	120	130		01 S. Main 01 S. Main 980.495.2 exultengin
	NOTES 1. EXIST SURVEY I TO BE 3'	ING UNDERGR NFORMATION. BELOW EXIS	OUND UTILI VERTICAL TING GROUNI	TIES ARE SH LOCATION I D.	OWN HORIZONT S UNKNOWN AN	ALLY PER D ASSUMED 360	NC License #C-4445 www.e
						350	≤
						340	ENTS
						360	
							CE FA IMPRO ORTH
						350	PEAR VAY _ LE, N
						340	OADV
						360	ROL
						350	
						340	
						360	
						750	
							ADW/ SEC1
						340	ROSS
						360	U
						350	
						340	
						360	VIE DATE
						350	ED BY: G. BC INIT
						340	DESIGN
							D.: 00103002 10/23/24 IONS
						330	JOB NG SCALE: SHEET NO.
80	90	100	110	120	130		X-8

	120	120	110	100	00	00	70	<u> </u>
	130	120		100	90	80		80
360								
350								
340								
360								
350								
340								
360								
350								
340						`		
360								
350								
550								
340							•• ••• ••• ••• •••	
700								
360								
350								
340								
360								
350								
3/0								
J4U								
330								



0.028 0.028 3:7

₩Q.



0.072









80	90 NOTES 1. EXIS SURVEY TO BE 3	100 S: TING UNDERG INFORMATION ' BELOW EXIS	110 ROUND UTILI VERTICAL STING GROUNE	120 TIES ARE SH LOCATION 1	130 IOWN HORIZON S UNKNOWN A	TALLY PER ND ASSUMED 360	Image: Notice state Image: State Image: State MC License 301 S. Main Street #C-4445 880.495.2250 www.exultengineering.com
						350 340 360 350 340 360	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						350 340 360 350 340 360 350	ROADWAY CROSS SECTIONS
						360 350 340 330	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 10/23/24 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT. DATE NOT PATE NOT PATE NOT PATE

	130	120	110	100	90	80	70	60	50	
360										
350										
340										
360										
350										
340										
360										
350										
									EX.EC	
340										
700										
350										
								•		
340										
360										
350										
340										
360										
350										
340										
530										
	130	120	110	100	90	80	70	60	50	



23+58.00

 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U
 U</t

23+65.00





80 90 100 110 120 130 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SHOWN HORIZONT. SURVEY INFORMATION. VERTICAL LOCATION IS UNKNOWN AN TO BE 3' BELOW EXISTING GROUND.	ALLY PER D ASSUMED 360	Image: Non-Structure Image: Structure Image: Structure
	350 340 360 350 340 360	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
	350 340 360 350 340 350 350	ROADWAY CROSS SECTIONS
	360 350 340 330	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 1023/24 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT. DATE
80 90 100 110 120 130		sheet no. X—10

	130	120	110	100	90	80	70	60	
360									
350									
340									
360									
750									
350									
340									
360									
350									
340									
330									
	130	120	110	100	90	80	70	60	



	130	120	110	100	90	80	70	60	
370									
360									
350									
340									
330									
350		- EX.EOP							
				• • • FO			• <u></u> • FO		
340									
330									
360									
									_L4 SEE _L∠
350									
						• FO• FO			
340									
330									
350								5	L4 SEEL4-
							• • F(>● FO	
340									
770									
550									
350				EX.ROW			SEE -L4- STA. 2 SEE -L4- CRO	23 + 32.00 SS-SECTIONS	5
		+			• • FO	• • f0 • f0	• L •f0	• — — • FO _ oc	• •
340									5
330									
	130	120	110	100	90	80	70	60	



80 90 100 110 120 130 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SHOWN HORIZON SURVEY INFORMATION. VERTICAL LOCATION IS UNKNOWN A TO BE 3' BELOW EXISTING GROUND.	TALLY PER ND ASSUMED	Image: Constraint of the constraint						
	370 360 350 340 330	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA						
	340 330 360 350 340 330	ROADWAY CROSS SECTIONS						
енерони и политични и в политични и поли	330 350 340 330	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT DATE SHEET NO. SHEET NO. SHEET NO.						
360	130	120	110	100	90	80	70	60 5
-------------	-------------	-----	-----	-----	----	----	----	------
350								
7.40								•FO
330								
360								
350								
740								
330								
360								
350								
340								
330								
360								
350								
340								
330								
360								
350								
340	GASe Carlos							
3 50								
	130	120	110	100	90	80	70	60 5











80	90 100 110 120 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SHOW SURVEY INFORMATION. VERTICAL LOCATION IS TO BE 3' BELOW EXISTING GROUND.	130 360 N HORIZONTALLY PER UNKNOWN AND ASSUMED 350	NCLicense B X U T ® NC License 301 S. Main Street 800.495.2250 800.495.2250 800.495.2250 MC License 980.495.2250 www.exultengineering.com
		340 330 360 350 340 330	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
		360 350 340 360 360 350 340 340	ROADWAY CROSS SECTIONS
		360 350 3350 3350 3350 130	DATE: 102324 EVIEWED BY: E. LYNCH SCALE: SCALE: NIII DATE HINII. DATE SHEET NO. SHEET NO. SHEET NO. SHEET NO. SHEET NO.

		100		100				
360	130	120			90	80	/0	60
350								
7.40								
540								
330								
350								
340								
330								
350								
340								
770								
330								
350								
240								
540								
330								
350								
340								
330								
360								
350								
							· · · · · · · · · · · · · · · · · · ·	
540								
330								
	120		110	100				













80	90 NOTES: 1. EXIST SURVEY I TO BE 3'	100 ING UNDERGROU NFORMATION. BELOW EXISTIN	110 120 ND UTILITIES ARE VERTICAL LOCATION NG GROUND.	130 SHOWN HORIZONT IS UNKNOWN AN	360 FALLY PER ND ASSUMED 350	Image: Non-state Image: Non-state <th< th=""></th<>
					340 330 350 330 330	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
					340 330 350 340 330 330 330	ROADWAY CROSS SECTIONS
				130	360 350 340 330	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: SCALE: HIT. DATE SHEET NO. SHEET NO. TALE SHEET NO.

	130	120	110	100	90	80	70	60	50
360									
350									
340									
3 30									
350									
									• FO
340									
330									
350									
340									
770									
550									
350									
340									
330									
350									
7 40									
540									
330									
50									
340									
3 30									



o∉£0⁰FO



n 0.020

15+40.00

0.018 0.018

0.042

•**#**£0











80	90 1 NOTES: 1. EXISTING SURVEY INFO TO BE 3' BE	00 110 GUNDERGROUND UTIL DRMATION. VERTICA LOW EXISTING GROUN	120 130 ITIES ARE SHOWN HORI. L LOCATION IS UNKNOW	ZONTALLY PER N AND ASSUMED 360	E E L T B B N L T B N G I N NC L T T T MC B S S S MC B S S S MC S S S S MC S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S M S S S S S S S S S S S S S <td< th=""></td<>
				350 340 330	FARM PROVEMENTS RTH CAROLINA
				350 340 330	PEARCE ROADWAY IMI ROLESVILLE, NOF
				350 340 330 350 340 330 350	ROADWAY CROSS SECTIONS
				340 330 350 340 330	NO.: 00103002 DESIGNED BY: G. BOYLE E: 102324 REVIEWED BY: E. LYNCH LE:

340 330 350 340 350 340 330 340 330 340 330 340 330 340 350 340 350 340 350 340 350 340 350 340 350 340 350 350 350 350 350 350 350						
330 350 340 340 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 350 360 350 350 350						
330 350 340 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 350 350 350 350 350 350						
330 350 340 340 350 340 350 340 350 340 350 340 350 340 350 340 350 340 350 360 340 350 350 350 350 350 350 350 350						
350 340 340 350 350 340 350 340 350 340 350 340 350 340 340 340 350 360 340 350 350 360 350 350 350 350 350 350 350						
350 340 330 330 340 350 340 340 340 340 340 340 340 340 340 340 340 350 360 340 350 350 360 350 350 350 350 350 350						
340 330 350 340 340 340 340 340 340 340 360 360 350						
340 330 350 340 350 340 350 340 350 340 350 340 350 340 350 360 350 350 360 350 350 350 350 350 350 350 350 350 350						
350						
350						
340 340 330 360 350 340 350 340 350 350 340 350 350 350 350 350 350 350 350 350 350						
340						
340						
330						
3.30						
360 350 340 330 360 360						
360 350 340 330 330 360						
360 350 340 330 360 360						
350						
350 340 330 360 350						
340 330 360 350						
340 330 360 350						
340 330 360 350						
330 360 350						
330 360 350						
360						
360 350						
350						
350						
350						
340						
330						
350						
340						
330						



80	90 NOTES: 1. EXISTIN SURVEY INF TO BE 3' B	100 110 NG UNDERGROUND UTIL FORMATION. VERTICA ELOW EXISTING GROU	120 13(ITIES ARE SHOWN HO L LOCATION IS UNKN ND.	D 350 RIZONTALLY PER OWN AND ASSUMED 340	E N L T NC License 301 S. Main Street 80.495.2250 MC License 980.495.2250 #C-4445 www.exultengineering.com
				330 350 340 330 350 340	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
				330 360 350 340 330 360 350 350	ROADWAY CROSS SECTIONS
			120 13(330 350 340 330	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: SCALE: BHEET NO: PATE NOI SHEET NO: CALE: BHEET NO: CALE: CA

	130	120	110	100	90	80	70	60
340								
330								
320								
310								
330								
320								
310								
330								
320								
310								
330								
320								
310								
330								
320								
310								
330								
320								
310								



80	90	100	110	120	130		N E E R I N G S. Main Street polis, NC 28081 80.495.2250 ultengineering.com
	NOTE: 1. EXIS SURVEY TO BE S	S: STING UNDERG INFORMATION 3' BELOW EXIS	ROUND UTIL. . VERTICA TING GROUN	ITIES ARE SH L LOCATION : D.	HOWN HORIZON IS UNKNOWN A	TALLY PER ND ASSUMED 340	NC License #C-4445 www.exu
						330	√ Z
						320	AENTS AROLI
						310	RARM CVEN C
						330	NORT NORT
						200	PEA NWAY ILLE,
						520	ROAF
						310	ž
						330	
						320	
						310	S Z
						330	VAY CTIOr CTIOr
						320	OADV SS SE
						.310	CRO ^R
						330	
						320	
						310	G. BOYLE E. LYNCH
						330	SIGNED BY:
						320	3002 DE 24 REV
						310	B NO.: 0010: ATE: 1023 ALE: REVISIONS
80	90	100	110	120	130		역 칩 였 · · · · · · · · · · · · · · · · · ·

	130	120	110	100	90	80	70	60	50
340									
3.30									
320									
310									
330									
320						× _∼			
310									
330									
320									
310									
330									
320									
310									
330									
320									
310									
330									
320									
310									
	130	120	110	100	90	80	70	60	50









80	90 100 110 120 130 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SHOWN HORI SURVEY INFORMATION. VERTICAL LOCATION IS UNKNOW TO BE 3' BELOW EXISTING GROUND.	Marca Marca Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction Correction
		330 330 Soadway improvements Olesville, North Carolina
		310 330 330 320 330 330 330 330 33
		310 330 320 310 310 310 310
80	90 100 110 120 130	330 310 310 310 310 310 310 310 310 310

	130	120	110	100	90	80	70	60
Z //								
540								
770								
550								
700								
520								
310								
330								
320								
310								
330								
320								
310								
330								
320								
310								
3.30								
320					· · · · · · · · · · · · · · · · · · ·	\		
7.0								
330								
320								
310								



							E R I N G n Street NC 28081 .2250 neering.com
80	90	100	110	120	130		G I N E 301 S. Mai (annapolis, w.exultengi
	NOTE 1. EXI SURVEY TO BE	S: STING UNDERG INFORMATION 3' BELOW EXIS	ROUND UTIL . VERTICA STING GROUN	ITIES ARE SH L LOCATION I ID.	IOWN HORIZON S UNKNOWN A	TALLY PER ND ASSUMED 340	NC License #C-4445 ww
						330	∠ Z
						320	AENTS
						310	RARM ROVEN CVEN
						330	NORT
						320	PEA DWAY 1LLE,
							ROAI
						310	Ř
						330	
						320	
						310	S Z
						330	WAY CTIO
						320	ROAD SS SI
						310	CRO
						330	
						320	
						310	Y: G. BOYLE A: E. LYNCH INIT. D/
						330	DESIGNED B REVIEWED B1
						320	0103002
						310	JOB NO.: C DATE: 1 SCALE: REVISION!
80	90	100	110	120	130		SHEET NO.

350	130	120	110	100	90	80	70	60	50
340									
330									
320									
340									
330									
350									
340									
330									
320									
340									3.1
330									
320									
340									
330									
320									
340									
330									
320									
310									
	130	120	110	100	90	80	70	60	50





0.018

0.020

0.003

۱ • FO



18+25.00



20

●**₽**⊕⊖ <u>₽</u> ●F⊖ ●F⊖

30

0.004

• FO

• FO • FO 328.71

•FO

10



10

20

30

•FO •FO

• F**0**FO • FO

40

50

60

70

80	90 100 NOTES: 1. EXISTING UNDER SURVEY INFORMATIO TO BE 3' BELOW EXI	110 GROUND UTILI N. VERTICAL STING GROUNI	120 TIES ARE SHO LOCATION IS	130 DWN HORIZON S UNKNOWN A	350 TALLY PER ND ASSUMED 340	Image: Construction Image: Construction Image: Construction NC License 301 S. Main Street 800.495.2250 #C-4445 980.495.2250 www.exultengineering.com
					330 320 340	ARM DVEMENTS H CAROLINA
					330	PEARCE F/ VAY IMPR(LE, NORTH
					350 340	ROADV ROLESVIL
					330	
					320	
					340 330	AY TIONS
					320	ROADW DSS SEC
					340	Č
					330 320	
					340	SOYLE YNCH DATE DATE
					330	DESIGNED BY: G. I REVIEWED BY: E. L INIT.
					320 310	VO.: 00103002 10/2324 :: 1 SIONS
80	90 100	110	120	130		REET NO. X-20

	130	120	110	100	90	80	70	60
350								
7.40				•				·····
540								
330								
350								
340								
330								
320								
340								
330								
320								
340								
3 30								
320								
					EOP			
340								
330								
320								
340								
550								
320								















80	90	100	110	120	130		ULLT® NEERING Main Street o.495.2250 Itengineering.com
	NOTE 1. EXI SURVEY TO BE	S: STING UNDER(INFORMATION 3' BELOW EXI	GROUND UTIL N. VERTICA STING GROUN	ITIES ARE SH _ LOCATION I D.	IOWN HORIZON S UNKNOWN A	ITALLY PER IND ASSUMED 350	NC License #C-4445 www.exul
						340	
						330	AENTS
						350	RARM ROVEN H CA
						340	RCE F IMPR NORT
						330	PEA DWAY ILLE,
							ROAD
						320	R S
						340	
						3.30	
						320	S
						340	(AY CTION
• • • • • • • •						330	S SEC
							CROS
						320	
						340	
						330	
						320	BOYLE YNCH DATE
						340	WED BY: G. WED BY: E.I INIT.
						330	2 DESIG
						320	NO.: 0010300 : 102324 E: /ISIONS
80	90	100	110	120	130		DATE: SCALE SHEET NO.
							X-21

≠ +++ ++++ +++++

	130	120	110	100	90	80	70	60
360								
						EX.ROW EX.ROW		
350				/				
			• FC	P FO	WATERo			•F9F0
340								
330								
350				• == == •= •				
340								
330								
350								
340								
330								
750								
550								
340								
330								
350								
340								
330								
350								
340								
3.30								













80	90	100	110	120	130		KULTR GINEERING 301 S. Main Street annapolis, NC 28081 980.495.2250 v.exultengineering.com
	NOTE: 1. EXIS SURVEY TO BE 3	S: STING UNDERG INFORMATION 3' BELOW EXIS	ROUND UTIL VERTICA STING GROUN	ITIES ARE SH L LOCATION 1	HOWN HORIZON IS UNKNOWN A	NTALLY PER AND ASSUMED 360	NC License #C-4445 WWW
						350	S NA
						340	
						330	FARN PROVE
						350	N N N N N N N N N N N N N N N N N N N
						340	ADWA SVILLE
						330	ROLE
						350	
						340	
						3 30	
						350	ADWA SECT
						340	ROSS
						330	O
						350	
						340	
						330	30YLE YNCH DATE
						350	SNED BY: G. F WED BY: E. L INIT.
						340	02 DESIC
						330	3 NO.: 001030 TE: 102324 ALE: EEVISIONS
80	90	100	110	120	130		직접었다 sheet NO. X—22

	130	120			90	80	/0	60
360								
350								TCE
340								
330								
350								
340								
360								
350								
340								
360								
350								TCE
340								
330								
350						EX.ROW		-L3- STA. 10+50 SEE -L3- CROSS-SEC 4. 4. 7. 7. 7. 7.
340							•FO	•
360								
350								
340								
330								
	120	120	110	100	00	80	70	40

















	1.00	10		110	100	00		70	40	
360	130	12	0			90	80	/0	60	
350										
340										
330										
350										
340										
330										
360										
750										
350										TCE
										† †
340										-1
330										
350										
340									╺	_
330										
			Image: Sector							
350									 	
									<u> </u>	
340									<u>→</u> →	
330										
350									J.	
									<u> </u>	
340										
330										
						+++++++++++++++++++++++++++++++++++++++				+















80	90 100 110 NOTES: 1. EXISTING UNDERGROUND U SURVEY INFORMATION. VERT TO BE 3' BELOW EXISTING GF	120 130 TILITIES ARE SHOWN HORIZONT ICAL LOCATION IS UNKNOWN AN ROUND.	360 ALLY PER ID ASSUMED 350	Image: Constraint of the second state of the second stress of
			340 330 350 340 340 330	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
			350 340 3350 350 3350 3350	CROSS SECTIONS
			330 350 340 330	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: SCALE: HEET NO. SHEET NO. SHEET NO. SHEET NO.

	130	120	110	100 90	0 80	70	60
750							
350							
340							
5-0							
330							
350							
340							
330							
350							
340							
330							
350							
550							
340							
330							
350							
340							• • • • • • • •
330							
350							
340							
550							
	130	120	110	100 90) 80	70	











80	90 100 110 NOTES: 1. EXISTING UNDERGROUND UTI SURVEY INFORMATION. VERTIC TO BE 3' BELOW EXISTING GROU	120 130 ILITIES ARE SHOWN HORIZONTALLY PER CAL LOCATION IS UNKNOWN AND ASSUMED UND. 350	 ► C L L T ® ► C L L T ® ■ B N G I N E E R I N G ■ 301 S. Main Street Kannapolis, NC 28081 980.495.2250 www.exultengineering.com
		340 330 330 350	EARCE FARM AY IMPROVEMENTS E, NORTH CAROLIN
		340 330	ROADW ROLESVILL
		350	
		330	ADWAY SECTIONS
		340	CROSS
		350 340	
		330	DESIGNED BY: G. BOYLE REVIEWED BY: E. LYNCH INIT. DA
		340	JOB NO.: 00103002 DATE: 102324 SCALE: REVISIONS PHEET NO'
80	90 100 110	120 130	J X-25

	120	120	110	100	00	80	70	40	50	40	20	20		10		0 20	20	10	60	40	
	130				90	80		60	50	40	30	20				0 20) 30	40	50	60	
50																					
40										<i>TCE</i>	× × 2.7 1 3:1		d0 3'X3 0.034 -	0.034	0.003	EX.EOP	EX.ROW				
30											331.10			29 +5	0 00		• • • • • • • • • • • • • • • • • • •				
20																					
40										TCE	₩0 ₩ ₩ ₹:7 3:1	0:		0.020 E	0.017	E		EX. POW			
30										33:	2.48°FØFO °F	CAR ST	CASo -	29 + 0	0 00		CASo	FO			
20																					
40										TCE	MQ 2 3 1 0.026	0.0	20	0.020 °	0.015	EX.EOP		E X. ROM			
30											•F 9 FO •Ff	FO		0 336.15	5 00		CASo				
20														20+0	5.00						
40										PDE	мон х. Э. З.1	0.0		0.027 0.027	0.001		Ex.EOP				
30										333. 9FO	•F@FQFO			0 ⁷ 222 28 ⊥ 5	0 00		CASe	PFO			
20															0.00						
40										문 0.05	5 <u>1</u> 0.030	0.02	9	0.029	0.000	0.000 3:7					
30										• F(9)	FO® FO ● F® F0			28 + 2	0 00			D			
20																					
40									<i>TCE</i>	E Contraction of the second se	EX.ROW	0.032 -		0.032	0.001	0.001 3:7	Ex Bow				
30										•	0335.24 • F	3 FO		28+0	0.00		Gaso	O			
											-14-	- E	Bur	-lingt	on	Mills	Ro	7 <i>d</i>			















	90 100 110 120 130 NOTES: 1. EXISTING UNDERGROUND UTILITIES ARE SHOWN HORIZO SURVEY INFORMATION. VERTICAL LOCATION IS UNKNOWN TO BE 3' BELOW EXISTING GROUND.	Clicense #C-4445 Base Band E N G I N E E R I N G NC License #C-4445 301 S. Main Street Kannapolis, NC 28081 980.495.2250
		340 330 320 320 330 SOLESVILLE, NORTH CAROLINA 330 320
		340 330 320 340 340 340 330 320 340 330 320 340 330 340 330 320 340 330
<u> </u>	90 100 110 120 130	320 340 340 330 BKI C. BOYLE DATE: 1023324 REVIEWED BY: C. BOYLE DATE: 1023324 REVIEWED BY: C. BOYLE DATE: 1023324 REVIEWED BY: C. BOYLE SHEET NO. SHEET NO. 240 SHEET NO.

	130	120	110	100	90	80	70	6	60	50	40	30	20	10	0	10	20	30	40	50	60	70
340																						
330										TCE		X. ROW	0.03	0.033	76.005	EX.EOF						
700												40	• FO • FO		3308	• FO	GASo					
320														31+	80.00							
340															8	EX.EOP						
330										<i>TCE</i>	0.200		0.120 0.060	0.032 0.032	560 560 560 560 560 560 560 560 560 560	•••						
320														31+	65.00		GA					
340																						
330											<i>TCE</i>	WOW X.ROW	0.03	4 1 0.034	331.22 000.0 33	EX.EOP						
700												6.14 0	F0° F0		331.09	i o Fo	GASo					
320														31+	50.00							
340												MOC NO		EX.EOP	31.84	- EX.EOP		EX.ROW				
330												27.38	0.03	0.033		••F0						
320														31+	00.00							
340																EOP		ð				
330												2:7 - 3: 	0. 	037 0.037	.000.0 333 	· · · · · · · · · · · · · · · · · · ·	• • • • •					
320											3	28.62 i • FO	•FO •FO	30+	· 50.00)		CASe				
340												0.0 1 0.0	20 0.046	0.046	24 27 27 27 27 27 27 27 27 27 27 27 27 27	EX.EOP		EX.ROW				
330												• FO	•••		333.35	•FO		CASo CASo				
320												.[4-	- <i>B</i> i	30+ r in(100.00	, Mill	S	Road	1			
	130	120	110	100	90	80	70	6	60	50	40	30	20	10	0	10	20	30	40	50	60	70













80	90 NOTES 1. EXIS SURVEY TO BE 3	100 S: TING UNDERGRO INFORMATION. ' BELOW EXIST	110 UND UTILI VERTICAL ING GROUND	120 FIES ARE SHO LOCATION IS	130 DWN HORIZON S UNKNOWN A	TALLY PER ND ASSUMED	Image: Constraint of the second strengt www.exultengineering.com Image: Constraint of the second strengt
						340	S NA N
						330	MENT: AROLI
						320	FARM PROVE
						340	ARCE , NOR
						330	PE
						320	RO ROLE
						340	
						330	
						320	S
						340	AY CTION
						330	OADW SS SEC
						320	CROS
						340	
						770	
						550	ATE
						320	3Y: G. BOYLE Y: E. LYNCH INIT. D/
						340	REVIEWED B
						330	00103002 10/23/24 NNS
						320	DOB NO.: SCALE: SHEET NO.
80	90	100	110	120	130		X-27

	130	120	110	100	90	80	70	60		50		40	30		20		10		0		10	2	0	30		40	50	6	0	70
340																														
													MOL				EX.EOP				- EX.EOP									
330																						• _	· ·	•						
320																	3	3 +	- <u>5</u> 0	.00)			GAS						
340																														
																	X.EOP		60		EX.EOP			MOA						
330													EX.ROW					.023	330	0.006		 0								
320					•											• FØFO	3	3 +	25	.00)									
340																	EOP.				EOP.			x, ROW						
330													- EX.ROW		3:1	0.020		.020	- 330.1	0.005										
320														0	FO	FO	3	3 ⊥	330.00	0(-0	GASo							
340																					EOP			ROW						
330													TCE - EX.ROW		3:1	0.02	9 0	.029	330.31	0.008	- EX.	~ ~_								
700									• • • •					• • • • • •	0	• FO			330.18	^		FO								
320																	3	2 +	- 30	.0(
340																					do									
330											33 10 1		EX.ROW	0.1	30 0.0	70	0.033	0.033	330.75	0.010	- EX.E									
).240	0	e FO	• FO		2 1	33063) 	FO	GASo							
320														1-	- [Bu	د ۱۲/۱	z + NG	,to	.u.	M	i//e	5 /	Ro	ad					
	130	120	110	100	90	80	70	60		50		10	30		20		10		0		10	2	0	30		40	50	6	0	70











80	90 100 NOTES: 1. EXISTING UNDE SURVEY INFORMATI TO BE 3' BELOW E	110 120 RGROUND UTILITIES ARE ON. VERTICAL LOCATIO XISTING GROUND.	130 SHOWN HORIZONTALLY PER N IS UNKNOWN AND ASSUMED	Image: Constraint of the second street Image: Constraint of the second street Source and second street Source and second street Source and second street NC License 301 S. Main Street Source and second street
			3.30	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
			340 330	
			320	S Z
			340	ADWAY SECTIO
			330	CROSS
			340	
			3.30	
			320	Y: G. BOYLE : E. LYNCH INIT. DAT
			340	DESIGNED B REVIEWED B
			320	JOB NO.: 00103002 DATE: 10/23/24 SCALE: REVISIONS
80	90 100	110 120	130	SHEET NO. X-28

	130	120	110	100	90	80	70	60	50
360									
350									
340									
360									
350									
340									
360									
350									
340									
360									
350									
340									
360									
350									
340									
360									
350									
340									
	130	120	110	100	90	80	70	60	50











80	90 100 NOTES: 1. EXISTING UNDE SURVEY INFORMATI TO BE 3' BELOW E	110 120 RGROUND UTILITIES ARE ON. VERTICAL LOCATIO XISTING GROUND.	130 SHOWN HORIZONTALLY PER IN IS UNKNOWN AND ASSUMED 360	Image: NC License #C-4445 Image: Street R I N G B R I N
			350 340 360 350 350 350 340 340	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
			350 340 360 350 340 360 350 350 340	ROADWAY CROSS SECTIONS
			360 350 340 130	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT: DATE SHEET NO'

	130	120	110	100	90	80	70	60
360								
350								
340								
360								
350								
340								
360								
350								
340								
360								
350								
340								
360								
350								
340								
360								
350								Щ.
340								
330								
	130	120	110	100	90	80	70	60





















80	90	100	110	120	130		U L T ® N E E R I N G S. Main Street polis, NC 28081 0.495.2250 iltengineering.com
	NOTES 1. EXIS SURVEY TO BE 3	S: STING UNDERC INFORMATION 3' BELOW EXI	GROUND UTIL: N. VERTICAL STING GROUN	ITIES ARE SH _ LOCATION I D.	IOWN HORIZON S UNKNOWN A	TALLY PER ND ASSUMED 360	NC License #C-4445 www.ext
						350	∠ Z
						340	
						360	H CARA
						350	ACE F IMPR NORT
							PEAF WAY LLE, r
						340	ROAD
						360	۳ <u>۵</u>
						350	
						340	
						360	
	VAY					350	NON NON
						350	ADWA
						340	RO
						360	Ū
						350	
						340	
						360	DATE
							Y: G. BOYLE Y: E. LYNCH INIT.
						350	DESIGNED B
						340	0103002
						330	JOB NO.: 0(DATE: 10 SCALE: REVISIONS
80	90	100	110	120	130		sheet no. X—30

	130	120	110	100	90	80	70	60
370		120						
360								
350								
370								
360								
350								
370								
<i>Si</i> 0								
360								
350								
340								
J40								
330								
370								
700								
360								
350								
340								
370								
360								
350								
340								











80	90 NOTE: 1. EXIS SURVEY TO BE (100 S: STING UNDERG INFORMATION 3' BELOW EXIS	110 ROUND UTIL VERTICAI	120 ITIES ARE SH LOCATION I	130 HOWN HORIZON S UNKNOWN A	370 ITALLY PER IND ASSUMED 360	Image: Constraint of the second state of the second state second state of the second state
						350 370 360 350 370 370	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						350 350 340 330 370 370 360 350 350	R CROSS SECTIONS
						370 370 360 350 340	JOB NO:: 00103002 DESIGNED BY: G. BOYLE JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE:: 102324 REVIEWED BY: E. LYNCH SCALE:: INIT: SCALE: INIT: SHEET NO. INIT: DATE: INIT: DATE: INIT: DATE: INIT: TAM INIT: TAM INIT: DATE: INIT: DATE: INIT: DATE: INIT:

	130	120	110	100	9(80	70	60	50	40	30	20		10	0	0	20	30	40	50	60	71
370																						
360																						
											MO2 	0.030 +	0.	030	8. 55 55 0.020	EX.EOF	0.020				SITE '	
350											351.58	otel otel			35263	OTENTEL	0 0					3 BY MC.
340														25+	20.00		EK GA					
770																						
570																						
360							EX.EOP			CENTA	UR ROAD					(.E0P						
350							•				0.023		0.0	022	9: 55: 0.020			0.020				
															325	• TEU TEL	GAS o UNK					
340														25+	00.00							
370																						
700								NON 400														
											EX.ROW	22.36		0.020	* 6. 75 55 6. 0.020		EX.ROW					
350											•	ELOTEL			352.76	•TEL •TEL						IS BY M
370														24+	50.00		EE G					
360											TCE	2.26	EX.EOP		08.2	EX.EOP	2.24 Brow			MON GORA		
350												• TEL	0.020	0.020	6.020 9 9 9 9 9 9 9 9 9 1 1 1 1 1 1 1 1 1 1	0.020		0.020	3:1			
770														24+			• LIAL • NAL					
570															00.00							
360											TCE EX.ROW	2	к.ЕОР		9	K.EOP	0		33			
350												352.1		0.020				3:1				
												OTEL	O TEL		355	• TEUTEL						
and the second														23+	-75.00							
340																						
340																						













$ \begin{array}{cccccccccccccccccccccccccccccccccccc$																										
$\frac{1}{10}$		130 120	0 11	0	100	90	0	80	70	60	50	40	30	20	10	0	10	20	30	· · · · · · · · · · · · · · · · · · ·	10 5	50	60	70	80	90
-L5 - Burlington Mills Road																										NOTES
$\frac{1}{26}$																										1. EXIST SURVEY I TO BE 3'
-L5- Burlington Mills Road																										
$ \frac{17}{32} $ $ \frac{1}{32} $ $ \frac$																										
$ \frac{10}{10} $																										
$\frac{1}{30}$	370																									
$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} $																										
$ \frac{1}{30} + \frac{1}{30}$	360																					MON A				
$\frac{100}{100}$ $\frac{1}{100}$ $$												TCE K.ROW		EX.EOP		04.	EX.EOP				2	024				
300	350												2:7 3:1	0.026	0.026	0.020		0.020			0.02	.0	3	.7		
$\begin{array}{c} 30 \\ 30 \\ 30 \\ 30 \\ 30 \\ 30 \\ 30 \\ 30 $													348.36	o _{TEL} ^o TEL		3514	' • • тĘ	atel								
$\frac{27 + 00.00}{30}$ $\frac{30}{30}$ $\frac{1}{30}$	340														97.				EX GAS ELEV UNK							
so so so so so so so so so so																00.00										
$ \frac{1}{30} $ $ \frac{1}{30} $ $ \frac{1}{30} $ $ 26+50.00 $ $ \frac{1}{30} $ $ $	370																									
$ \frac{560}{360} $ $ \frac{560}{360} $ $ \frac{26+50.00}{360} $ $ \frac{560}{360} $ $ \frac{560}$																										
$\frac{1}{300}$ $\frac{1}$	360																0					ROP ROW				
$\frac{1}{30}$												TC EX.ROW		- EX.EOF		551.75	- <i>EX.EOF</i>		NOM			<u>م</u>				
$\frac{1}{360}$ $26 + 50.00$ $\frac{26}{9}$ $\frac{26}{$	350												2:1 3:1	0.025	0.025			0.020				.0	3:	1		
$ \frac{340}{26+50.00} \\ \frac{26}{50} \\ \frac{6}{50} \\$													349.10	o _{TEL} o TEL			•TĘ	O TEL	• • • •							
$\frac{370}{360}$ $\frac{1}{26+00.00}$ $\frac{1}{360}$ $\frac{1}{26+00.00}$ $\frac{1}{360}$ $\frac{1}$	340														26+	50.00										
$\frac{370}{360}$ $\frac{1}{360}$ $$																										
$\frac{1}{350}$ $\frac{1}{350}$ $\frac{1}{360}$ $\frac{1}{360}$ $\frac{1}{360}$ $\frac{1}{360}$ $\frac{1}{360}$ $\frac{1}{350}$ $\frac{1}$	370																									
$\frac{360}{350}$ $\frac{360}{360}$ $\frac{360}{360}$ $\frac{360}{370}$ $\frac{360}{360}$ $\frac{360}{350}$																						8				
$\frac{1}{350}$ $\frac{1}{360}$ $\frac{1}$	360											TCE		do			do					A DAA				
$\frac{350}{26+00.00}$ $\frac{2}{303}$ $\frac{2}{5}+50.00$ $-L5- Burlington Mills Road$												EX'	<i>?:1</i> 3:1	0.028 0	0.028	07.756 0.020		0.020	EX.ROW		<u>2</u> 0.02	0				
$\frac{340}{26+00.00}$ $\frac{360}{360}$ $\frac{360}{350}$ $\frac{360}{350}$ $\frac{360}{360}$ $\frac{360}{350}$ $\frac{360}{35$	350												349.84			22500	• • TE				_		3:7			
$\frac{340}{370}$ $\frac{360}{360}$ $\frac{3}{50}$ 5																			GAS O CAS O UNK							
$\frac{370}{360}$ $\frac{360}{350}$ $\frac{360}{350}$ $\frac{360}{376}$	340														26+0	00.00										
$\frac{360}{350}$																										
$\frac{360}{350}$ $\frac{3}{340}$ $\frac{3}{25+50.00}$ $\frac{3}{25+50.00}$ $\frac{3}{25+50.00}$ $\frac{3}{25+50.00}$ $\frac{3}{25+50.00}$	370																									
$\frac{350}{360.58} \xrightarrow{0.027}{0.027} \xrightarrow{\frac{1}{9}}{0.020} \xrightarrow{\frac{1}{9}}{0.02$																										
350 340 -L5-Burlinaton Mills Road	360											EX.ROW		X.EOP			X.EOP									
33058 отвыть в отвы	750												2.7 3.1	0.027 0.	.027	0.020		0.020	EX.R	SE	SITE DRIVEW	AY CADAMS				
340 -L5- Burlington Mills Road	330												350.58	•TEb _{TEL}			і • те,	► ► -								
-L5- Burlington Mills Road	340														75 1	50 00			EX GAS UNK							
-L5- Burlington Mills Road	J4U															50.00										
-L5- Burlington Mills Road																										
													-/ 5	Rur	lina	$t \cap n$	1/1	°// c	<i>P</i> ∧	nd						
130 120 110 10 90 80 70 60 50 40 30 20 10 10 20 30 40 50 60 70 80 90 80 90 10 90 10 90 10 10 10 10 10 10 10 10 10 10 10 10 10		130120	0 11	0	100	90	0	80	70	60	50	40			10	1 U1 1 0	1 VI 10				405	50	60	70	80	90









								® L	E E R I N G lain Street s, NC 28081 95.2250 ngineering.com
	80	90 NOTES: 1. EXISTIN	G_UNDERGROU	IIO JND_UTILITI	120 ES ARE SHOWN	HORIZONTALL	Y PER	Т X Ц	E N G I N F 301 S. N Kannapoli 980.4) www.exulter
		SURVEY INF TO BE 3' BI	ORMATION. ELOW EXISTI	VERTICAL L NG GROUND.	OCATION IS UN	NKNOWN AND A	SSUMED	׀]]	NC License #C-4445
									INA
							370		
						3	360		PROVI RTH (
						3	350	L (2	
						3	340	Ż	SVILLI
							370		ROLE
							360		
1						3	350		
						3	340		(0)
							370		AY TION:
							360		S SEC
									CROS
							550		
							340		
							370		
							360	E. LYNCH	
						3	350	DESIGNED BY: REVIEWED BY:	
							340	0103002 1	
								JOB NO.: 00 DATE: 10 SCALE: DIVICIONIC	
70	80	90	100	110	120	130		X	SHEET NO.

	130	120	110	100	90	80	70	60 !
370								
360								
350								
340								
370								
360								
350								
340								
370								
360								
350								
340								
370								
360								
350								
340								
330								
	130	120	110	100	90	80	70	60 !





	130	120	110	100	90 80	70	60 5
370							
360							
350							
340							
370							
360							
350							
340							
370							
700							
350							
370							
360							
350							
340							
	130	120	110	100	90 80	70	60 5



80	90 100 NOTES: 1. EXISTING UNE SURVEY INFORMAT TO BE 3' BELOW	110 DERGROUND UTILI TION. VERTICAL EXISTING GROUNE	120 TIES ARE SHOW LOCATION IS	130 VN HORIZONTA UNKNOWN AND	LLY PER ASSUMED	NC License 301 S. Main Street MC License 301 S. Main Street Monor 980.495.2250 Monor 980.495.2250
					370 360 350 340 370	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
					360 350 340 370 360 350 340	ROADWAY CROSS SECTIONS
					360 350 340	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: SCALE: HEET NO: SHEET NO. SHEET NO. SHEET NO.

770	130	120	110	100	90	80	70	60 5
370								
360								
350								
340								
370								
700								
350								
340								
370								
360								
350								
340								
370								
360								
350								
340								
370								
360								
350								
3/0								

80	90 NOTES 1. EXIST SURVEY I TO BE 3'	100 ING UNDERG NFORMATION BELOW EXIS	110 ROUND UTILI . VERTICAL STING GROUNE	120 TIES ARE SH LOCATION I	130 IOWN HORIZON S UNKNOWN A	370 TALLY PER ND ASSUMED 360	NCLicense B X U T ® NC License 301 S. Main Street 80.495.2250 980.495.2250 www.exultengineering.com
						350 340 370 360 350 340	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						370 360 350 340 370 360 350	ROADWAY CROSS SECTIONS
				120		370 360 350 340	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: SCALE: NOI SHEET NO. SHEET NO. SHEET NO. SHEET NO.

	130	120	110	100	90	80	70	60
370								
360								
750								
350								
370								
360								
350								
5.50								
370								
360								
350								
370								
700								
350								
370								
360								
350								
7.40								
540								
370								
360								
350								
340								

PDE TCE

350 360 360 360 360 360 360 360 36	80	90 NOTES 1. EXIST SURVEY TO BE 3	100 : ING UNDERGI INFORMATION BELOW EXIS	110 ROUND UTILIT VERTICAL TING GROUND	120 IES ARE SH LOCATION I	130 OWN HORIZON S UNKNOWN A	370 TALLY PER ND ASSUMED 360	Image: NC License #C-4445 Image: Sign Sign Sign Sign Sign Sign Sign Sign
340 350 350 350 350 350 350 350 35							350 370	M /EMENTS CAROLINA
370 360 350 360 360 360 360 360 360 360 36							360 350	PEARCE FAR VAY IMPROV LE, NORTH
350 370 360 350 360 360 360 360 360 360 360 36							370 360	ROADW ROLESVIL
360 350 370 360 360 370 360 370 360 370 360 370 360 370 360 370 370 360 370 370 370 370 370 370 370 370 370 37							350 370	
370 360 360 340 370 360 340 370 360 340 370 360 340 360 370 360 340 360 370 360 340 360 360 340 360 360 360 360 360 360 360 36							360 350	AY TIONS
360 350 350 340 370 340 370 1 360 1 360 1 360 1 360 1 360 1 360 1 360 1 360 1 350 1 340 1 340 1 340 1							370	ROADW CROSS SEC
340 370 370 370 360 360 350 350 340 340							360 350	
360 360 350 SHEET NO. 340 SHEET NO. 340 340 SHEET NO.							340 370	BOYLE YNCH DATE
SCALE: SCALE: SCALE: SCALE: SCALE: STOLE SHEET NO.							360 350	02 DESIGNED BY: G. 4 REVIEWED BY: E. 1 INIT
						120	340	JOB NO.: 001030 DATE: 10/23/24 SCALE: REVISIONS PHEET NO.

	130	120	110	100	90	80	70	60	5
360									
350									
340									
330									
360									
350									
340									
330									
360									
350									
340									
330									
360									
350									
370									
360									
560									
550									
540									
				100					

80	90 NOTES 1. EXIS SURVEY TO BE 3	100 5: TING UNDER INFORMATION BELOW EXI	110 GROUND UTIL N. VERTICA STING GROUN	120 ITIES ARE SH LOCATION 1 D.	130 HOWN HORIZON IS UNKNOWN A	NTALLY PER AND ASSUMED	Image: Non-angle information Image: Non-angle information Image: Non-angle information NC License 301 S. Main Street Street MC License 301 S. Main Street Street MC License 980.495.2250 Street MC License www.exultengineering.com
						360	₹
						350	AENTS
						340	FARM ROVEN CA
						330	NOR1
						360	PEA DWAY VILLE,
						350	ROA
						740	
						540	
						330	
						360	SNS SNS
						350	DWAY SECTIG
						340	ROA OSS
						330	CR
						360	
						350	
						370	LE DATE
						360	D BY: G. BOY D BY: E. LYNG INIT.
						350	DESIGNE
						<i>ZA</i> Ω	O.: 00103002 10/23/24 SIONS
80	00	100	110	120	120	540	DATE: SCALE: SHEET NO.
				140			X-38

	120	120	110	100		<u> </u>	70	
860		120			90			
50								
340								
30								
860								
50								
340								
30								
50								
240								
860								
50								
10								
860								
50								
640								
360								
50								
540								
30								

80	90 NOTES	100 S: STING_UNDERG	110 ROUND_UTIL:	120 ITIES ARE SI	130 HOWN HORIZON	360	EXULT ENGINEERING 301 S. Main Street Kannapolis, NC 28081 980.495.2250 www.exultengineering.com
	SURVEY TO BE 3	INFORMATION B' BELOW EXIS	. VERTICAL STING GROUN	_ LOCATION :	IS UNKNOWN 4	AND ASSUMED 350	NC License #C-4445
						340	TS LINA
						330	M EMEN CARO
						360	E FAR
						350	EARCI AY IN E, NO
						340	DADWESVILL
						330	ROL
						350	
						340	
						360	SZ
						350	WAY CTIOI
						340	ROAD SSS SI
						360	CRO
						350	
						340	
						360	YLE LCH DATE
						350	VED BY: G. BC /ED BY: E. LYN INIT.
						340	02 DESIG
						330	3 NO.: 001030 TE: 102324 ALE: tevisions
80	90	100	110	120	130		ସ୍ଟ୍ରୁଅୁୁୁୁୁୁ SHEET NO. X_39

	130	120	110	10	0	90	80	70	(50	50
360											
350											
340											
360											
										-	
350						++++					
340											
330											
360											
										-	
350											
340											
330											
360											
										-	
550											
7 4 4											
540											
700											• TEL
560											
550											
540											
330											

80	90 100 NOTES: 1. EXISTING UNDEF SURVEY INFORMATIC TO BE 3' BELOW EX	110 GROUND UTILITI N. VERTICAL L ISTING GROUND.	120 1 ES ARE SHOWN OCATION IS UN	30 HORIZONTALLY PER KNOWN AND ASSUMED 360	Image: Constraint of the constraint
				350 340 360 350 350 340 330	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
				360 350 340 330 360 350 350 340	ROADWAY CROSS SECTIONS
				350 340 330	JOB NO:: 00103002 DESIGNED BY: G. BOYLE DATE: 10/23/24 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT. DATE
80	90 100	110	120 1	30	SHEET NO. X-40

	130	120	110	100	90	80	70	60	50
360									
350									
340									
330									
360									
350									
							- EX.EOF	- EX.E0F	
340							+		
							EK WATEL		
360									
350									
340									
							O TEL		
330									
200									
560									
350									
340									
330									
360									
350									
340									
770									
5.50									
	130	120	110	100	90	80	70	60	50

0.004

0.009

0.004

°T6LTEL

0.020

								L T ® R I N G treet 28081 50 ering.com
80	90	100	110	120	130			I N E E I S. Main S napolis, NC 980.495.22 xultengine
	NOTE 1. EXI SURVEY TO BE	S: STING UNDERG INFORMATION 3' BELOW EXI	ROUND UTILI I. VERTICAL STING GROUN	TIES ARE SH LOCATION T D.	HOWN HORIZON IS UNKNOWN AN	TALLY PER ND ASSUMED 360		NC License #C-4445 www.ex
VAY ICADAMS						350		SINA
						340		A EMENT CAROL
						330		FARA PROVI RTH (
						360		EARCE AY IM E, NOI
	SITE D					350		PI ADW, SVILL
		BY MCADAMS				340		ROLES
						360		
						350		
						340		NS
						330		ECTIO
						360		ROAD OSS S
						350		CR
						340		
						330		
						360	BOYLE LYNCH	DATE
						350	SIGNED BY: G. 'IEWED BY: E.	
						340	03002 DE 324 REV	
						330	JOB NO.: 001 DATE: 102	SCALE: REVISIONS
80	90	100	110	120	130			SHEET NO.

	130	120	110	100	90	80	70	60	5
370									
360									
350									
340									
370									
360									
350									
340									
370									
360									
350									
340									
330									
360									
350									
340									
330									
	130	120	110	100	90	80	70	60	5

							RING RING 28081 50 ering.com
80	90 NOTES 1. EXIS SURVEY TO BE 3	100 5: STING UNDERG INFORMATION ' BELOW EXI:	110 ROUND UTIL I. VERTICA STING GROUN	120 ITIES ARE SH L LOCATION I	130 HOWN HORIZON IS UNKNOWN A	ITALLY PER ND ASSUMED	NC License #C-4445 www.exultengine
						370 360 350 340 370	PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
						360	
						350	
						340	SNO
						370	DWAY
						360	ROA ROSS
						350	U
						340	
						330	
						360	. BOYLE LYNCH I. DATE
						350	SIGNED BY: G
						340	33002 DE: 324 REV
						330	JOB NO.: 001C DATE: 10/2: SCALE: REVISIONS
80	90	100	110	120	130		SHEET NO. X-42

	60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 1 NOTES:	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	1. EXISTING UNDERGROUND UTILITIES ARE SHOWN SURVEY INFORMATION. VERTICAL LOCATION IS UN TO BE 3' BELOW EXISTING GROUND.	HORIZONTALLY PER KNOWN AND ASSUMED
360		360 SL
350 340	⁴ ⁴ ⁴ ⁴ ⁴ ⁴ ⁴ ⁴	320 APROVEMEN APROVEMEN APROVEMEN
360 350	2 4 5 5 5 5 5 5 5 5 5 5 5 5 5	350 SVILLE, NO
340		340 340
360 350	L L L L L L L L L L L L L L L L L L L	360 350
340		340 330 SNOIL
360		360 SEOSS SEOS
350 340	$\frac{1}{2} + \frac{1}{2} + \frac{1}$	350
370 360		370 360
350 350 		DESIGNED BY: G. BOY REVIEWED BY: E. LYNC INIT.
340 330 330		B NO:: 00103002 B NO:: 00103002 TE: 102324 ALE: ReVISIONS
130 120 110 100 90 80 70	-L5- Burlington Mills Road 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 1	SHEET NO. 30 X−43

770	130	120	110	100	90	80	70	60
370								
360								
350								
340								
360								
350								
340								
360								
340								
360								
350								
540								
360								
350								
340								
360								
50								
340								
530								

80	90 100 NOTES: 1. EXISTING UNDER SURVEY INFORMATIO TO BE 3' BELOW EX:	110 120 GROUND UTILITIES ARE SHO N. VERTICAL LOCATION IS ISTING GROUND.	130 JWN HORIZONTALLY PER S UNKNOWN AND ASSUMED 360	Image: Construction Image: Construction NC License 301 S. Main Street MC License 301 S. Main Street MC License 980.4955.2250 Mc-4445 www.exultengineering.com
			350 340 360	ARM DVEMENTS H CAROLINA
			350	PEARCE FA ADWAY IMPRO SVILLE, NORTH
			360 350	ROLE
			340 360	S
			350 340	ROADWAY SS SECTION
			360 350	CRO
			340 360	YLE ICH DATE
			350	02 DESIGNED BY: G. BO REVIEWED BY: E. LYN INIT.
80	90 100	110 120	<i>330</i> 130	JOB NO:: 0010300 DATE:: 102324 SCALE: REVISIONS

	130	120	110	100	90	80	70	60
70								
160								
50								
050								
870								
860								
50								
370								
60								
50								
370								
860								
250								
50								
\$70								
160								
50								
70								
860								
50								
\$40								

							J L T ® E R I N G in Street NC 28081 5.2250 sineering.com
80	90 NOTES	100 S:		120			E N G I N E 301 S. Ma 800.490 www.exulteng
	SURVEY TO BE 3	INFORMATION 3' BELOW EXI	I. VERTICAL STING GROUN	LOCATION	IS UNKNOWN A	ND ASSUMED 370	NC License
						360	× Z V
						350	AENT
						370	FARM ROVE/ TH C
						360	NOR1
						350	PEA DWAY 1LLE,
							ROAI
						370	ž
						360	
						350	
						370	ZS
						360	WAY CTIO
						350	SS SE
						370	CRO
						.360	
						750	
						350	
						370	: G. BOYLE E. LYNCH INIT. DA
						360	DESIGNED BY
						350	103002
						340	JOB NO:: 00 DATE: 10' SCALE: REVISIONS
80	90	100	110	120	130		SHEET NO. X-45

	130 12	20	110	100	90	80	7	0	60	50	0	3	30	20		10		0		10		20		30		40	5	0	60	70
390																														
370																								*						
													X X			- EX.EOF					EX.EOP			EX.R						
360																		32				•								
													i otel					363			CAS GAS FI FV FI FV	• TEL								
380																Ľ	51 +	- 5(0.0)0	E E E E E E E E E E E E E E E E E E E									
370																														
													X.ROW			<u>ЕХ. ЕОР</u>					Х.ЕОР			EX.ROW						
360																					₩ + + +			-						
													i I OTE					362.01				● TEL								
350																Ę	51 +	- 00	0.0)0	<u> </u>									
370																														
																EOP								M						
200												X.ROW				EX.					EX.E									
360																		60.47				EQ TEL	• •	 1 TEL						
750														• TEL					^ ^		EX GAS	× S								
350																			U.L	JU										
													F		D ,		•	~+			/ •									
	130 14	20	110	100	00	80	7	0	60	50	0		\mathcal{O}^{-}	- L	JU	1/ / . 10	1179	<u>)</u> [(UN	/ / 10	VI I	15	- M	U	U	40		0	60	70
	· · · · · · · · · · · · · · · · · · ·				///			-			-			<u> </u>						10		<u> </u>		~~				-		

90 NOTES: 1. EXISTI SURVEY IN TO BE 3' F	100 NG UNDERGROU FORMATION. BELOW EXISTIN	110 120 ND UTILITIES ARE VERTICAL LOCATIO IG GROUND.	130 SHOWN HORIZONTALLY PEI N IS UNKNOWN AND ASSUM	E C L Image: Second stress of the second st
				PEARCE FARM ROADWAY IMPROVEMENTS ROLESVILLE, NORTH CAROLINA
			380 370 360 380 380 380 380 380 380 380	CROSS SECTIONS
			370 360 350	JOB NO.: 00103002 DESIGNED BY: G. BOYLE DATE: 102324 REVIEWED BY: E. LYNCH SCALE: REVISIONS INIT. DATE